Tender Inviting Autority: CDM & PHO Kandhamal.

NAME OF THE PROJECT:- CONSTRUCTION OF DAY CARE SUBCENTRE - CUM - HEALTH & WELLNESS CENTRE AT SRIRAMPUR UNDER KOTAGARH BLOCK OF KANDHAMAL DISTRICT FOR THE YEAR 2021-22 Amount put to tender Rs. 2,370,246.00 SCHEDULE OF WORKS SI. Description of work No.or Unit Estimated Rate No. AMOUNT Figure Qty. Words Rs. P CIVIL WORK Earth work in excavation of foundation in hard or gravel soil with initial lead and lifts including dressing and leveling the bed and depositing the excavated earth at places away from work site 1 with all leads and lifts including cost of all labour, cess and T&P and dewatering if required for the work etc. Complete as directed by the Engineerin charge 1.01 Ground Floor 69.51 Cum 188.77 Supplying & filling good clean river sand inside 13121.40 the foundation / plinth of approved area including watering to complete saturation & ramming complete with all leads & lifts including cost, 2 conveyance, royalty, cess & taxes of all materials & cost of all labour & T&P required for the work complete (measurement will be taken for compacted section) as per direction of Engineerin-Charge. 2.01 Ground Floor 57.16 One Cum Cement Concrete of proportion (1:3:6) in 519.20 29677.47 foundation and floors using 4cm size clean hard 3 black broken granite stone metal of approved quality and from approved quarry including hosting lowering and laying concrete in layers not 3.01 Ground Floor 17.94 One Cum 5037.28 RCC of design mix of M-20 grade of controlled 90368.80 qulity having cube strength of 250kg./cm2 in design mix with minimum quantity of cement as specified in IRC Code of 150 mm. cubes at 28 days curing after mixing & tests conducted in accordance with relevant clauses of IS 456/IS 516/IRC 16/1987/IRC-78/1983 using crusher 4 broken hard granite course aggregate of 10 mm. to 20mm. sizes & proportion as specified in clause-302.6.2 of IRC 21/1987, IS-10262 & subject to mix design in conformity with the grading & proportion of different materials for concrete as specified in the relevant codes of approved 4.01 Column Base & Grade Beam (Ground Floor) 12 94 4.02 Column in Super structure (Ground Floor) One Cum 5798.23 75029.10 6.41 One Cum 12971.92 4.03 column First Floor 83150.01 1.63 One Cum 14520.79 4.04 Plinth Band/Grade Beam 23668.88 3.68 4.05 One Cum Lintel (Ground Floor) 6153.26 22644.00 2.49 4.06 One Cum Wall Beam & T-Beams(Ground Floor) 9333.94 23241.51 5.34 One Cum 4.07 12971.92 Roof Beam First Floor 69270.05 0.77 4.08 Chajja & fins (Ground Floor) One Cum 14520.79 11181.01 3.03 4.09 One Cum Chhaja First Floor 838.08 2539.38 7.02 One Cum 4.1 Stair case (Ground Floor) 937.74 6582.93 1.53 Roof Slab (Ground Floor) 4.11 One Cum 11025.46 16868.95 7.99 4.12 One Cum First Floor Slab 9928,79 79331.03 1.84 Supply of HYSD bars confirming to approved One Cum 10869.03 19999.01 grade cutting bending , binding, lapping, splicing, welding etc. (conforming to ISI specification) & jointing if necessary by lapping & tying the grills & placing in position as required for RCC works as per the approved design, hoisting, lowering & laying position including cost & conveyance, Cess of tor steel & binding wires of 18 to 20 5 gauge (as approved by the Deptt.) etc. complete (Weight of binding wire shall not be considered for payment at all which will be bome by the contractor (standard CO-efficient of different size of the steel shall be considered & welding & lapping should confirm to relevant clause of IRC -21/1987) as per direction of the Engineer in charge. 5.01 Ground Floor 43.56 5.02 One Qtl First Floor 8,941.77 389503.50 5.94 One Qtl 8,965.39

1) 2 hay 0 12/201 son con 03/12/2014 son con

1

53254.42 IN Toll allow 1 122

6	K.B. brick masonary in cement mortar (1:4) ir foundation and plinth and basements and cemental floor bed plinth molding and similar such types of works with all necessary projections using K.B. bricks of (23 cm x 11 cm x 8 cm) size having crushing strength not less than 75Kg. Per Sqcm. Including splays, cutting, circular moulding, chamfering corbelling watering curing for 7 days after immersing the bricks in water for six hours before use etc. complete including cost, conveyance of all materials and labour, royalty, cess with T&P required for the work with all taxes and royalties etc. with all T&P complete in all respect as per direction of the Engineer in charge.					
6.01	Ground Floor	19.31	One Cum	105100		
7	K.B. brick masonary in cement mortar (1:6) in foundation and plinth and basements and cemental floor bed plinth molding and similar such types of works with all necessary projections using K.B. bricks of (23 cm x 11 cm x 8 cm) size having crushing strength not less than 75Kg. Per Sqcm. Including splays, cutting, circular moulding, chamfering corbelling watering curing for 7 days after immersing the bricks in water for six hours before use etc. complete incluling cost, conveyance of all materials and labour, royalty, cess with T&P required for the work with all taxes and royalties etc. with all T&P complete in all respect as per direction of the Engineer in charge.			n 4,354.60		84087.33
7.01	Ground Floor	37.38	One Cum	4 440 00		
7.02	First Floor	9.15	One Cum		1.1	165100.73 42837.58
8	12mm thick cement plaster (1:4) over brick work including cement punning and Bitumen painting on top including, watering and curing with cost and conveyance of all materials and labour, cess with T&P required for the work with all taxes and royalties, Cess etc. complete in all respect in all floors as per direction of the Engineer in charge.					
0.04	One of Fl					
8.01	Ground Floor	141.97	One Sqm	145.76	2	20693.55
0.02	First Floor	59.06	One Sqm	151.24		8931.94
9	16 mm thick grading plaster (1:4) finished smooth on roof slab including, watering and curing with cost and conveyance of all materials and labour, cess with T&P required for the work with all taxes and royalties, Cess etc. complete in all respect in all floors as per direction of the Engineer in charge.					
9.01	Ground Floor	507.47	One Sqm	206.31	1	104696.14
9.02	First Floor	21.92	One Sqm	211.19	2.15	4629.33
10	Supplying, fitting and fixing Vitrified tile in floors of approved make conformaing to IS:13755 laid on 20 mm thick cement mortar (1:4) and filling joints with white cement of approved quality including cost of all materials, etc. required for the work all complete as per direction of E.I.C.					7020.00
10.01	Ground Floor	88.20	One Car	077.00		
10.02		00.20	One Sqm	977.63		86226.97
	Fixing tiles in dados skirting and risers of steps on 12mm thick CP (1:3) jointed with neat cement slurry mixed with pigments to match the shade of					
11	the tiles including cost, carriage, cost of all labour etc. complete.					
11	the tiles including cost, carriage, cost of all labour	61.61	One Sqm	1,028.44		63362.19

(n) Balang on 12/2021

SA Cart Wind al D.12-07.12-

12	cement primer including all labour, materials etc. complete.					
12.01	Ground Floor	587.83	One Sqm	58.51		34393.93
12.02	First Floor	59.06	One Sqm			3599.12
12.03	First Floor	21.92	One Sqm			1314.54
13	Wall painting 2 coats with plastic emulsion paint of approved shade on new work to give an even shade including cost of paint etc complete.					1011.01
13.01	Ground Floor	445.86	0	77.00		
13.02	First Floor	21.92	One Sqm	77.33		34478.35
14	Wall painting two coat with any approved weather coat paint including cost of all materials, labour and T&P require for the work etc. complete as directed by the E.I.C.	21.92	One Sqm	78.90		1729.49
14.01	Ground Floor	141.97	One Sqm	71.07	-	10000.01
14.02	First Floor	59.06	One Sqm	73.67		10089.81 4350.83
15	Supplying of M.S. Door, Window with grills, Grills made out of M.S. Angle frame, M.S. Flat, Sheet etc of approved section & design, electrically welded properly with all necessary locking arrengement, and 1 coat red oxide primer including cost of all materials, labour charges, carriage of materials to site etc. complete.					
15.01	Ground Floor	105.00	0.0			
15.02	Ground Floor	195.08	One Sqm	76.15		14855.25
15.03	First Floor	311.10 296.76	One Sqm One Sqm	80.29 76.15		24978.22
16	mm thick circular pipe with Balustrade of size 32 mm x 32mm x 2mm @ 0.90 mtr C/C and stainless aquare pipe bracing of size case as per approved design and specification, buffing, polishing etc. with the cost, conveyance taxses of all material, cost of all labour etc. complete in all respect.				3	
16.01	Ground Floor	4.50	One Sqm	3,682.09		
17	Supplying and fitting-fixing of Un-plasticised Poly Vinyl Chloride (UPVC) (FENESTA/ NCL VERA LTD Casement Door - 60- Series duly manufactured using UPVC reinforeced profiles of 60mm x 55 mm x 25 mm for outer frames, 102 mm x 80 mm for casement Door Sash Profile and 74 mm x 60 mmx2 5mm mullion profile capable of mounting single glazing system structurally reinforced with hot dip galvanised up to 50 microns of minimum thickness of 2.0 mm prefabricated & welded through fusion welding the door sash shall be fited with 12mm thick WPC Board of Greenply make duly fixed with EPDM weathering seal resistant accessories like cliping locking system made of aluminium 1 No per set of sashes and the system is to be installed at the side using anchor fasteners,					16569.41
	silicone rubber sealant, easy glazing / deglazing at side etc.including cost andconveyance of all materials conforming to ASTM D 638-421477-95 and the applicable codes and standards.As per specification approved by the Department & as per derection of the E.I.C. SE No 16100 dt					

m Babay 2021 07/12/2021 Sty Gu 67/12/2021

4

97

12. 0 7:12:2021 0 7:12:2021 0 7:12:2021

				ORK	197352.00
				ORK	 1975387.00
otal estima	ted cost in Figures		CIVIL	WORK	 1975386.74
		1	One Sqin	346.71	 5100.10
20.02	First Floor	14.71	One Sqm		31287.77
20.01	Ground Floor	98.13	One Sqm	318.84	
20	25mm thick CC 1:2:2 with 6mm size CB chips for grading concret over roof slab etc. complete.		one oqui	135.06	1064.27
19.01	First Floor	7.88	One Sqm	135.06	 2435.13
19.01	Ground Floor	18.03	One Sqm	135.06	
19	Painting two coats with approved enamel paints of approved colour, shade over a coat of primer including sand papering, polishing the surface, cost, conveyances of all materials and cost of all labour etc, complete as per specification & direction of E.I.C.				00210.44
	Painting two costs with annual	11.48	One Sqm	5,767.46	66210.44
18	Supplying, fitting, fixing up window (sliding type) made up aluminum Section 151-154, 151-155, as windows frame section No. 151- 155, 151-153 and 151-167 as shutter framewith 5mm thick black glass as panel fitted with rubber beading including locking arrangement including all fitting including cost of materials all taxes labour, T&P etc. complete as per direction of Engineer- incharge.				

kh seventy thousand two hundred forty six only)

12/2021 Asst. Engineer NHM,Kandhamal

My Quoted rate is to the Estimated Cost

% (Both in Figure and words) excessover/ Less than/ Equal to

CDM & PHO Kandhamal

Notes:

5

Signature of the Contractor

(1) The contractor should not write any thing except quoting of percentage and in case anything else regarding tender rate is mentioned, the

(2) Strike out which are not applicable.

July Strath shar word

VU 202



Sninompun

	PH WORK	*			
SI No	Description of items	Qty	Unit	Rate	Amount
1	Supplying all materials, labour, T&P and providing and fixing to wall or				, anoune
	ceiling and floor IS marked galvanised mild steel tubes (medium grade)		1	1 s = 5	
	confirming to IS: 1239/1990, part-1 of the following nominal bore, tube	1	$ _{\mathcal{T}} \leq _{\mathcal{T}}$		
	fittings and clamps including making good the wall, ceiling and floor,				
	testing all complete as per specification and direction of the Engineer in				
	charge				
	in Ground Floor				
а	25 mm dia G.I pipe	6.0	Mtr	294.40	1766.
b	32 mm dia G.I pipe		Mtr	362.10	2172.
	in First Floor			502.10	21/2.
a	25 mm dia G.I pipe	8.0	Mtr	298.60	2388.
b	32 mm dia G.I pipe		Mtr	366.90	3302.
C	32 mm dia G.I pipe		Mtr	372.40	4096.
d	40 mm dia G.I pipe (For inter Connection)		Mtr	450.90	5410.
2	Supplying all materials, labour, T&P and providing and fixing to wall or			450.50	5410.
	ceiling and floor C-pc pipes and pipe fittings of the following nominal			. E. S	
	borewith clamps including making good the wall		1.1		
	testing all complete as per specification and direction of the Engineer in	*			
	charge				
	In ground floor	1 2 2 2 2			
а	20 mm C-PVC pipes	6.00	Mtr	198.30	1100 (
b	25mm C-PVC pipes		Mtr		1189.8
	in First Floor	5.00		276.20	2485.8
а	20 mm C-PVC pipes	6.00	Mtr	202.50	
b	25mm C-PVC pipes		Mtr	203.50	1221.0
3	supplying all materials, labour, T&P and cutting holes through existing	0.00	IVICI	281.40	2251.2
	brick work including making good the damages in cement mortar (1:4)	$\mathbb{R}^{2n} \to \mathbb{R}^{n}$			
	for taking G.I. Pipes and fittings/ P.V.C. pipes and fittings etc. all				
	complete as per P.H. specification and direction of E.I.C		5		
а	250 mm thick wall in GF	6.00	Each	22.20	
b	251 mm thick wall in GF		Each	32.20	193.2
4	supplying all materials, labour, T&P and cutting holes in R.C.C. floors,	5.00	Each	32.80	98.4
	roofs, erc. up to 19 Cm. thick for passing G.i. Pipes and fittings/ P.V.C.				
	pipes and fittings etc. and reparing the holes after insertion of nines		4 ⁴	-	
	etc. with cement concrete (1:2:4) including finishing complete so as to				
1.1	make it leak proof as per direction of E.I.C.				
	in ground floor	3.00	Fach		
5	Supplying all materials, labour, T&P and cutting grooves in pucca floors	5.00	Each	104.00	312.00
	and walls for taking G.I./P.V.C. pipes and making good the damages as	1.1			
	per direction of the E.I.C.				
1	n ground floor	6.00	N.44-		
6	Supplying all materials, labour T&P and fitting and fixing brass/CP	0.00	IVIT	131.10	786.60
1	ittings of the following nominal bore with supply of all joiniting materials				
c	complete as per specification and direction of the Engineer in charge				
			· ·		
				, , , , , , , , , , , , , , , , , , ,	
a 1	5mm dia Cp Long body bib cock jaquar make)	5.00			
b 1	5mm dia CP angle stop cock (jaquar make)	5.00		875.30	4376.50
c 2	Omm dia CP concealed stop cock (jaquar make)	5.00		612.70	3063.50
d 2	5mm dia brass or gun metal full way valve(shaktimake)	2.00		919.00	1838.00
e 3	2 mm dia brass or gun metal full way valve(shakti make)	3.00		909.90	2729.70
f 1	5mm dia CP Flange	2.00		1331.40	2662.80
	5mm dia CP Extention Nipple	5.00		40.30	201.50
	upplying all materials, labour, T&P and 67 with 15mm or 20mm inlet fitting and	6.00	ach	59.30	355.80
fi	xing CP shower specification and direction of the inclusion of the				
	xing CP shower specification and direction of the including Engineer polishing in harge all complete as per				
	or an animete as per			, - ¹ , 1 ,	
1	5mm dia CP revolving shower with 15mm and				
c l	5mm dia CP revolving shower with 15mm x 225mm a shower arm long size CP nower Arm	1000			
				See 18	
		2.00 E		458.30	

D Blog of Tyles y

Sikon Johnson

AL 10 201 7h

8	Supplying all materials, labour, T&P and Fixing Rotational Moulded				
	Polyethelene cylindrical water stroage tanks conforming to IS 12701-1996				
	Including cutting holes through the tank and fixing miled steel tubes and fittings				
	and providing extra socket and jam Nuts, Fixing Valves etc. including hoisting			1 1	
	upto a height of 5 mtr above ground level and placing the tank to the required				
	position and providing	1 A A	1 8 6		
	1000 litre capacity water storage tanks on roof of SF(without staging)				
9	Supplying soil waste ventilating all materials, pipes labour, and fittings T&P and	1.0	0 Each	8711.30	871
	of the fitting following and fixing outside U-PVC diameter SWR				
	conforming to ISI No 13592/1992 to walls with nails, bobbins and				
	wooden plugs or laving in transhes including in the			1 1	
	wooden plugs or laying in trenches including jointing with supply of				
	approved rubber lubricant by non-heat application method/as per		1		
	manufacturer's specification, testing, earthwork in excavation in all				
	kinds of soil and refilling of trenches as per specification and direction				
	of the engineer in charge		· · · · · · · · · · · · · · · · · · ·		
	110		×		
	110mm diameter U-PVC SWR pipes(Supreme/Ashirvad)	9.00	Mtr	284.20	255
	75mm diameter U-PVC SWR pipes(Supreme/Ashirvad)		Mtr	153.70	
	110mm U-PVC door Tee		Each		768
	110mm U-PVC offset			137.20	41:
	110mm U-PVC door bend		Each	115.20	345
	110mm U-PVC plain shoe bend		Each	131.70	790
	110mm U-PVC cowl		Each	186.50	373
	110mm P-trap	2.00	Each	38.40	76
	75mm U-PVC plain Tee	1.00	Each	225.00	225
	75mm U-PVC plain bend	1.00	Each	65.90	65
10		3.00	Each	49.40	148
10	Supplying all materials, labour T&P and cutting holels through existing				
	Drick or laterite masonry wall for taking H.C.I pipes and fittings including	1. B. 1			
	making good the damages etc. all complete as per P.H.Specification				
	and direction of the Engineer in charge		n 1620		
		ана 1910 г. – Салана 1910 г. – Салана			
	250mm to 375mm thick wall	6.00	Fach		
11	Supplying all materials, labour T&P and and fixing 10 liters capacity low	0.00	Laun	136.50	819
	level flushing cistern with a pair of cast iron or M.S. brackets complete			1	
	with fittings such as siphonic arrangements 15mm nominal size				
	brass/pvc ball valve with polythene float CP brass handle, unions and				
	Couplings for connection with inlet autility and a sublishing of the sublishing of t				
-	Couplings for connection with inlet, outlet and overflow pipes, 32mm dia				
	Cp Long flush bend, 15mm dia pvc inlet connection pipe including				
	cutting holes and making good the same and connecting the flush bend				
	with cistren and closet and connceting the inlet pipe with suupply main etc all				
	complete as per the specification and direction of the Engineer in				
1.00	charge				
				=	
	10 litres Capacity PVC cistren with 32mm dia flush bend				
	(Parryware/Hindware/Neycer/Rak)		1.1		
12	Supplying all materials, labour, T&P and fixing vitreous china water	2.00 8	ach	1279.90	2559.
	closet, squattingpan (Indian type W.C pan/Orissa pattern squatting				
	pan) duly embedded in compart commune (2 - 1 - 2				
	pan) duly embedded in cement concrete (1:5:10) using 4cm size hard		··· ·		
8	granite metal including fixing a pair of vitreous china 250mm x 130mm				
P	(30mm footrest, fixing 100mm dia HCl 'p' or 's' trap (with/without 50mm dia how) (and the second dia how) (and the sec				
le le	ha norn) for water colset squatting pan including jointing the trap with	· . · · ·	6		
4	Dan in cement mortar (1:1) cutting the floor and mending good the				
C C	amages etc all complete as per specification and direction of the				
E	ngineer in charge				
5	80mm size Orissa pan(Parryware/Hindware/Neycer/Rak)				<u></u> ;
13 S	upplying all materials, labour, T&P and fixing the following vitreous	1.00 E	ach	2080.10	2080.1
c	hina wash down water closet(European type W.C.pan) with integral 'P				
0	r'S' trap to the illor with wooder align type W.C.pan) with integral 'P				
	r 'S' trap to the illor with wooden plugs and chromium plated pedestal		< ¹		
S	crews including jointing the trap with soil pipe in cement				
	nortar(1:1)fixing plastic seat and cover for wash down water closet with				
In	promiting whether the	1			
C	momum plated brass hinges and rubber buffers including polishing				
C	hromium plated brass hinges and rubber buffers including polishing tc.all complete as per specification and direction of the Engineer-incharge				
C	tc.all complete as per specification and direction of the Engineer-incharge.				

() Bolog por

P7-12-224 Shon vz/m/m/ 10

Contraction of the second) r br

	E	uropean water closet with 'P trap plain(Parryware/Hindware/Neycer/Rak)			1	
			1.00	Each	2427.90	2427.9
1	a N	Supplying all materials, labour, T&P and fixing laboratory sink with outlet at end and weir overfiow including fitting and fixing a pair of cast iron or MS brackets painted white, fixing 50mm/40mm dia CP brass waste ixing 50mm/40mm dia PVC waste pipe 910mm long with supply of				
	w a	vooden plugs,screws and cement etc including cutting holes in walls and making good the damages etc all complete as per specification and direction of the Engineer in charge.				
Ne.	a	nu direction of the Engineer in charge.				
	6	00mmx450mmx200mm size Stainless steel Sink	1.00	Each	2336.40	2336.4
1	5 S	upplying all materials, labour T&P and fixing wash basins with hole for			2350.40	2330.4
	p h	illar taps with cast iron or M.S.brackets painted white including cutting oles in walls and making good the damages with supply of wooden lugs, screws and cement etc, fixing pedestal for wash basin recessed				
	5	50mmx400mm W.H.basin with porcelain pedestal & Jaquar make				
	fit	ttings(Parryware/Hindware/Neycer/Rak)	2.00	Each	3720.50	7441.00
1	6 SI	upplying all materials, labour, T&P and fixing mirror of superior glass		Lucii	5720.50	7441.00
	N	nounted on 6mm thick A.C.sheet or plywood sheet and fixed to /Ooden plugs with CP screws and washers complete as per pecification and direction of the Engineer in charge				
		00mmx450mm size B.E.mirror	2.00	Each	567.00	1121.0
17	br pl Er	upplying all materials, labour, T&P and fixing standard size glassshelf with CP rass brackets and guard rails complete fixed to wooden lugs with CP screws as per specification and direction of the ngineer in charge		Luci	507.00	1134.00
	60	00mmx125mm glass shelf with CP/NP guard rails	2.00	Each	524.80	1049.60
18	ra	upplying all materials, labour, T&P and fixing standard sized CP towel il complete with CP brass brackets fixed to wooden plugs with CP SCrews as			524.00	1049.00
	pe	er specification and direction of the Engineer in charge				
		5mmx600mm long CP towel rail	2.00	Each	648.10	1296.20
19	со	upplying all materials, labour, T&P and fixing CP soap holder omplete with CP brass brackets fixed to wooden plugs with CP screws per specification and direction of the Engineer in charge			0.10	1290.20
	CF	P soap holder	2.00			
20	Su	pplying all materials, labour, T & P and constructing Gully trap	2.00	Each	142.10	284.20
	ch	amber of the following inside size with 8 cm thick R.C.c. precast				
	CO	ver slab in CC (1:2:4) mix using 12mm size h.g. chips, foundation	~			
	co	ncrete (1:4:8) using 40mm sizeh.g. metal on bed aound trap. K.B.				
	bri	ickwork in CM (1:6) in P&F and inside 12mm thick cement plastering				
	(1:	3) finished ith a floating coat of neat cement including fixing				
	10	0mm x100mm size gully trap, 150mm x150mm C.I gratig etc. all			1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	
	co En	mplete as per aproved drawing, specification and direction of gineer in charge				8
	250	0mmx250mm with RCC cover	1.00	Each	1803.53	1803.53

Delas Belas Balas Suran Suran Stran Stran

10 Infront the

31		1.00	Eduli	Total	197507.7
21					
31	Supply and fitting &fixing of Plastic rope M.s cover cap etc	50.00		71.70	3585.0
30	Supply and fitting &fixing of sustable cable and connecting the Pump	E0.00	Mtr	71 70	
	set &testing etc	50.00	Mtr	119.50	5975.0
	Nippling and lowering to bore well making connection to pump				
29	Supply and fitting &fixing of HDPE Pipe and fiting with CP	1.00		1,10,00	14/3.0
	submersible Pump with commissioning and testing	1.00	Each	1475.00	1475.0
28	Supply and fitting &fixing of I.S.I make 1.00 HP single phase	1.00	Each	15849.15	15849.1
27	Supply and fitting &fixing of I.S.I make 1.00 HP single phase submersible Pump set to give discharge of 3000 Itr / hour	1.00	Fach	15040 45	400.0
27	Withdrawal of casing pipes	45.00	Mtr	199.50	8977.
	storein good condition.			N.	1 Paralle
	pipesfrom the unsuccessful boreand depositingin the departmental				
26	Supplying all materials, labour, tools and plant and withdrawing casing	0.20			1073.
D ₂	CC(1:2:4)with 12mm chips for grouting upto 5 mtr.Depth in sanitary		cum	5368.00	1073.
	Sanitary sealing upto 5mtrs below ground level.	1.00	Each	789.80	789.
	sanitary sealing(excluding cost of cement which willbe supplied by the Department).				
	pipe to be inserted in the bore into the rockthe bottom to ensure				
	per direction of the Engineer in charge. Minimum one metre of casin9				
	drawing)to plug the bore hole excluding cost of cement all complete as				
	GI/PVCIMS housing pipe upto 5 mtrs below ground level(as per				
	sanitary sealing by cement concrete grouting of annular space around		= ⁶ .	2	
25	Supplying all materials and labour, tools and plant and providing		19 - C		
	By DTH/Rotary Rig	1.00	Each	4994.50	4994.
24	Cleaing and developing the tube well with supply of compressor	30.00	WILL	950.80	28524.
	Cost of 125mm dia P.V.C schedule-80 pipe	30.00		138.20 950.80	4146. 28524.
	Plugging tube wells to prevent entry of foreign materials. Lowering of 125 mm dia GI/P.V.CMS casing pipes 0 mtr to 45 mtrs	20.00	N At-	100.00	
	Complete and keeping the top of casing pipe threaded including9				
	upplying and fixing all jointing materials, tools and plant etc all				
	ncluding cutting and threading of pipes and slotted pipes and				
	46.00m depth and fitted and fixed up in perfectly vertical position				
	without slotted pipes as per the necessity from ground level up to0				
23	Lowering the following size of G.I/P.V.C/M.S housing pipes with or				
	Drilling of 150mm dia bore 31mtr to 60mtr	30.00		540.50	16215.
2	Drilling of 200mm dia bore 0mtr to 30 mtr	30.00	Mtr	540.50	16215.
	supplied by the contractor for 400mm dia bore only		2 A		
	supplied by the contractor for 400mm dia bore only				
	lowering and withdrawing after completion of the tube well), 200mm dia to 400mm dia in overburden portion including packing of gravel				
	collapse of overburden is to be provided by the contractor including				
	boulder formation(G./P.V.C/M.S casing pipes if required to prevent				
	or without well screen as per the necessity for soft, medium, hard and		1.14		
	dia G.II/P.v.C/M.S casing pipes for housing fitted with socket and with		5		
	tools and plant and consumables etc for lowering of 125mm/100mm				
	of the Engineer in charge including use of own rig with its accessories,			-	
	combination rig as required to suit the site condition as per the direction		÷		
	unconsolidated rock with down the hole hammer drilling rig or		1.50		
22	specified depth below ground level through consolidated and				
22	Inside size 760mm x760mm x460mm Labour for drilling a perfectly vertical bore hole of specified dia for a	1.00	Each	6503.06	6503.
	per aproved drawing, specification and direction of Engineer in charge				
	materials to worksite, payment of royality, taxes etc. all complete as		-		1
	around the chamber including watering ,curing, conveyance of all		×_ 8 = * a		
	earth work in excavation in all kinds of soil and refilling the cavity		an a		
	slab in (1:2:4) using 12mm size h.g. chips with RCC man hole cover,	i de la g	git, hu -i		
	punning to inside, cementflush pointing (1:3) to outside, R.C.C. cover				
	12mm size h.g. chips, 12mm thick cement plastering (1:3) finished with	1			
	and shaping the channel inside and benching with CC (1:2:4) using				
	size h.g. metal on bed, Ist class K.B. brickwork in CM(1:6), moulding				
				1 1	

Delat 12 2021

- All

10 non the Sik Out

 \mathcal{N} Kox in

SI.	E.I. WORK						
No.	Description of Items		nit Q				
1	Recessed wiring to light point with 1.5 sq.mm FR PVC insulated single core multistrand copper conduct of ISI marked with 20 mm dia non-metalic PVC flexible conduit with EArry 050 kinetic copper conduct.			nty F	Rate		Amount
	of ISI marked with 20 mm dia non-metalic PVC flexible conduit with 5Amp, 250 V piano type modular switch ISI marked and ceiling rose ISI marked mounted on MO has the second seco	or					
3	of suitable size MS box with 1 sq mm ED to the intervention wis box having front Modular base & cove	r					
	earth wire including all accessories and connection or the angle core multistrand copper conductor as			B			
	Finolex/ L&T / Anchor / Havels /HPL/ V Guard)	e				1	
	,						
a							
b	-do- Group	A Poi	nt 1	5 463	3.38		6,
С	-do- Group	B Poi	nt s	688	8.68		6,
2	Recessed wiring to Fan Point indo- Group	C Poi	nt 8	970	0.14		7,
3	-do- Group	B Poi	nt 6	688	8.68		4,
						1	<u>т,</u>
4	-do- Group	C Poir	nt 1	970	.14		(
5 5	%/F of Angle holder replacing Ceilling Rose -do- Group	B Poir	nt 3	688	.68		
6 5	F of 5A. Modular Switch & 5A. Modular Socket outlet of ISI marked on existing board	Eac					2,0
	source outlet of ISI marked on existing board	1					2
78	/F of extension board of 6 modular Metal box with modular base & cover in recess including providing nd fixing of 2 nos of 3pin 5/6amp modular socket out let & 2 nos of 5/6 nm excess including providing	Eacl	h 8	222	.54		1,7
a	nd fixing of 2 nos of 3pin 5/6amp modular socket out let & 2 nos of 5/6 amp piano type modular switch, onnection, painting etc as required.	1	1	1			
8 9	onnection, painting etc as required.	Each	6	763.	.97		4,5
fi	/F of Power point with 4 modular metal box with modular base & cover in recess including providing and king of 5 pin 15/16 amp. piano type Modular switch & Socket connection and the second se	1-		+			
	entried a booker, connection, painting etc as required	Each	4	0.00	1		
S S	(F of Power point with 4 modulor 8 2 module		1 4	636.	1 80		2,5
pr	oviding and fixing of 5 pin 15/16 amp. piano type Modular switch & Socket & Mini DP MCB, ponnection, painting etc as required for AC	1	;				
CC	principal painting etc. as required for the spectrodular switch & Socket & Mini DP MCB	Each	1	1257.	02 İ		1.0
15/	F of 1 no of 5 pin 15/16 amp. Socket 4	1	i		1	ш.	1,25
Im	odular box with cover with connection, painting etc as required for Inverter connection			T	1		
				1			
S/	E of 18 SW/G Modules and the	Each	1	1174.	01		1 17
S/	F of 18 SWG Modular motol how of fully	Each		1174.	01		1,17
S/	F of 18 SWG Modular motol how of fully	Each		1174.	01		1,17
S/	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of odular base & cover in front including cutting the wall and making good the same in case of recessed nduit as required.		1	1174.	01		1,17
S/	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of odular base & cover in front including cutting the wall and making good the same in case of recessed nduit as required.			1174.	01		1,17
S/	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of odular base & cover in front including cutting the wall and making good the same in case of recessed nduit as required. 2 Modular box with base & cover	Each		1174. 			
S/	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of odular base & cover in front including cutting the wall and making good the same in case of recessed nduit as required. 2 Modular box with base & cover 4 Modular box with base & cover	Each	2	212.9	5		
S/	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of odular base & cover in front including cutting the wall and making good the same in case of recessed nduit as required. 2 Modular box with base & cover 4 Modular box with base & cover	Each	2		5		42
S/	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of odular base & cover in front including cutting the wall and making good the same in case of recessed nduit as required. 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover	Each	2	212.9	5		42 26
S/	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of odular base & cover in front including cutting the wall and making good the same in case of recessed nduit as required. 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover	Each	2 1 1	212.9	5 4 9 1		42 26
S/ Ma	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of odular base & cover in front including cutting the wall and making good the same in case of recessed anduit as required. 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover	Each Each Each	2 1 1 2	212.9 260.2 318.8 360.8	5 4 9 1 9		42 260 318
S/ Ma co	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of odular base & cover in front including cutting the wall and making good the same in case of recessed anduit as required. 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover	Each Each Each	2 1 1	212.9	5 4 9 3		42 260 318 721
S/ Ma	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of odular base & cover in front including cutting the wall and making good the same in case of recessed 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 13 Modular box with base & cover 14 Modular box with base & cover 15 Modular box with base & cover 16 Modular box with base & cover 17 Modular box with base & cover 18 Modular box with base & cover 19 Modular box with base & cover 10 Modular box	Each Each Each Each Each	2 1 1 2 7	212.9 260.2 318.89 360.83 473.49	5 4 9 3 1 0 9		42 26 318 72
S/ Ma co	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of odular base & cover in front including cutting the wall and making good the same in case of recessed nduit as required. 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover ing for circuit / sub-main wiring along with earth wire with following sizes of PVC insulated single core 2x1.5+1x1.0 (1.8)	Each Each Each Each	2 1 1 2 7 58	212.9 260.2 318.89 360.83 473.49 125.05	5 4 9 3 (9 		42 26 311 72 3,314
S/ Ma co	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of odular base & cover in front including cutting the wall and making good the same in case of recessed 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 2x1.5+1x1.0 (1.8) 2x1.5+1x1.5 (1.8.1)	Each Each Each Each Mtrs	2 1 1 2 7 58 90	212.9 260.2 318.89 360.83 473.49	5 4 9 3 (9 		42 26 31 72 3,31 7,252
S/ Ma co	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of odular base & cover in front including cutting the wall and making good the same in case of recessed a Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 2x1.5+1x1.0 (1.8) 2x1.5+1x1.5 (1.8.1); 2x2.5+1x1.5 (1.8.2)	Each Each Each Each Mtrs Mtrs	2 1 1 2 7 58 90 85	212.9 260.2 318.89 360.83 473.49 125.05	5 4 9 1 3 (9) 1 (9) 1 (9) 1 (9) 1 (9) 1 (9) 1 (9) 1 (9) 1 (9) 1 (9) 1 (1) 1 (9) 1 (1) 1 () 1 () 1 () 1 ()) 1 ()) 1 ()) 1 ()) 1 ()) 1 ()) 1 ()) 1 ()) 1 ()) 1 ()) 1 ()) 1 ()) 1 ()) 1 ()) 1 ()) 1 ()) () (42 26 311 72 3,314 7,252 11,346
S/ Ma co	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of bodular base & cover in front including cutting the wall and making good the same in case of recessed anduit as required. 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 2x1.5+1x1.0 (1.8) 2x2.5+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.3)	Each Each Each Each Mtrs Mtrs Mtrs	2 1 1 2 7 58 90 85 85	212.9 260.2 318.89 360.83 473.49 125.05 126.07	5 4 9 1 3 1 0 9		42 26 31 72 3,314 7,252 11,346 11,902
S/ Ma co	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of bodular base & cover in front including cutting the wall and making good the same in case of recessed 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 2x1.5+1x1.0 (1.8) 2x2.5+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.3) 2x6+1x2.5 (1.8.4)	Each Each Each Each Mtrs Mtrs Mtrs	2 1 1 2 7 58 90 85	212.9 260.24 318.89 360.83 473.49 125.05 126.07 140.03	5 4 9 3 1 2 9 1 1 9 1 1 1 1 1 1 1 1 1 1 1 1 1 1		42 26 31 72 3,314 7,252 11,346 11,902 13,379
S/ Ma co	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of bodular base & cover in front including cutting the wall and making good the same in case of recessed nduit as required. 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 2x1.5+1x1.0 (1.8) 2x1.5+1x1.0 (1.8) 2x2.5+1x1.5 (18.2) 2x4+1x1.5 (18.3) 2x6+1x2.5 (1.8.4) Inverter wiring (1x1.5smm) Copper wire (1.19.1)	Each Each Each Each Mtrs Mtrs Mtrs	2 1 1 2 7 58 90 85 85	212.9 260.24 318.85 360.83 473.45 125.05 126.07 140.03 157.41	5 4 9 3 1 2 9 1 1 9 1 1 1 1 1 1 1 1 1 1 1 1 1 1		42 260 318 721 3,314 7,252 11,346 11,902 13,379 13,571
S/ Ma co Wir	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of bodular base & cover in front including cutting the wall and making good the same in case of recessed anduit as required. 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 2x1.5+1x1.0 (1.8) 2x1.5+1x1.0 (1.8.1) 2x2.5+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.3) 2x6+1x2.5 (1.8.4) Inverter wiring (1x1.5smm) Copper wire (1.19.1) ing and other loads in the existing MCB Distribution board ISI marked complete with competion and the existing MCB Distribution board ISI marked complete with competion	Each Each Each Each Mtrs Mtrs Mtrs Mtrs Mtrs Mtrs Mtrs Mtrs	2 1 1 2 7 58 90 85 85 72 75	212.9 260.2 318.89 360.83 473.49 125.05 126.07 140.03 157.41 188.49 45.83	5 4 3 6 1 2 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		42 260 318 721 3,314 7,252 11,346 11,902 13,379 13,571
S/ Ma co WVir	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of bdular base & cover in front including cutting the wall and making good the same in case of recessed a 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 2x1.5+1x1.0 (1.8) 2x1.5+1x1.5 (1.8.1) 2x2.5+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.2) 2x6+1x2.5 (1.8.4) of 'B/C/D' series SP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for ng and commissioning etc. as required single pole (SP) (2.6.1)	Each Each Each Each Mtrs Mtrs Mtrs	2 1 1 2 7 58 90 85 85 85 72	212.9 260.24 318.89 360.83 473.49 125.05 126.07 140.03 157.41 188.49	5 4 3 6 1 2 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		42 26 311 72 3,314 7,252 11,346 11,902 13,379 13,571 3,437
S/ Ma co Win S/F ghti ghti	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of bdular base & cover in front including cutting the wall and making good the same in case of recessed anduit as required. 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 2x1.5+1x1.0 (1.8) 2x1.5+1x1.0 (1.8) 2x2.5+1x1.5 (1.8.1) 2x2.5+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.3) 2x6+1x2.5 (1.8.4) Inverter wiring (1x1.5smm) Copper wire (1.19.1) ing and cher loads in the existing MCB Distribution board ISI marked complete with connection, ng and commissioning etc. as required single pole (SP) (2.6.1)	Each Each Each Each Mtrs Mtrs Mtrs Mtrs Mtrs Mtrs Mtrs Mtrs	2 1 1 2 7 58 90 85 85 72 75	212.9 260.2 318.89 360.83 473.49 125.05 126.07 140.03 157.41 188.49 45.83	5 4 3 6 1 2 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		42 260 318 721 3,314 7,252 11,346 11,902 13,379 13,571 3,437
S/F ghti //F ghti onn	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of dular base & cover in front including cutting the wall and making good the same in case of recessed anduit as required. 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 2x1.5+1x1.0 (1.8) 2x1.5+1x1.0 (1.8) 2x4.5+1x1.5 (1.8.1) 2x4+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.3) 2x6+1x2.5 (1.8.4) 0 f 'B/C/D' series SP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for ng and commissioning etc. as required single pole (SP) (2.6.1) 0 f 'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for ng and other loads in the existing MCB Distribution board ISI marked complete with connection, 18 and other loads in the 2 Way double door MCB Distribution board ISI marked complete with 18 and tome loads in the 2 Way double door MCB Distribution board ISI marked complete with 18 and tome loads in the 2 Way double door MCB Distribution board ISI marked complete with connection, 19 and other loads in the 2 Way double door MCB Distribution board ISI marked complete with connection, 19 and other loads in the 2 Way double door MCB Distribution board ISI marked complete with connection, 19 and tome loads in the 2 Way double door MCB Distribution board ISI marked complete with connection, 19 and other loads in the 2 Way double door MCB Distribution board ISI marked complete with connection, 10 and tome loads in the 2 Way double door MCB Distribution board ISI marked complete with connection, 10 and the loads in the 2 Way double door MCB Distribution board ISI marked complete with connection, 10 and the loads in the 2 Way double door MCB Distribution board ISI marked complete with connection and the loads in the 2 Way double door MCB Distribution board ISI marked complete with connection and the loads in the 2 Way double door MCB Distribution boa	Each Each Each Each Mtrs Mtrs Mtrs Mtrs Mtrs	2 1 1 2 7 58 90 85 85 72 75 8	212.9 260.2 318.89 360.83 473.49 125.05 126.07 140.03 157.41 188.49 45.83 130.16			42 26 314 72 3,314 7,252 11,346 11,902 13,379 13,571 3,437 1,041.
S/ Ma co Wir S/F ght ssti /F ght pnn upp	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of dular base & cover in front including cutting the wall and making good the same in case of recessed 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 6 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 2x1.5+1x1.0 (1.8) 2x1.5+1x1.0 (1.8) 2x1.5+1x1.0 (1.8) 2x4.5+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.3) 2x6+1x2.5 (1.8.4) 10 0 0 f 'B/C/D' series SP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for 19 mg and other loads in the existing MCB Distribution board ISI marked complete with connection. 10 f'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for 19 and other loads in the 2 Way double door MCB Distribution board ISI marked complete with connection. 19 MIN Installation teeting 4 commissioning etc. as required (2.6.2a)+(2.3.1b)	Each Each Each Each Mtrs Mtrs Mtrs Mtrs Mtrs Mtrs Mtrs Mtrs	2 1 1 2 7 58 90 85 85 72 75	212.9 260.2 318.89 360.83 473.49 125.05 126.07 140.03 157.41 188.49 45.83	5 4 3 6 1 2 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		42 260 310 721 3,314 7,252 11,346 11,902 13,379 13,571 3,437 1,041.
S/F ghti ssti upp	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of dular base & cover in front including cutting the wall and making good the same in case of recessed 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 12 Modular box with base & cover 2x1.5+1x1.0 (1.8) 2x2.5+1x1.5 (1.8.1) 2x2.5+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.3) 2x6+1x2.5 (1.8.4) 1 Inverter wiring (1x1.5smm) Copper wire (1.19.1) ing and other loads in the existing MCB Distribution board ISI marked complete with connection, of 'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for ng and commissioning etc. as required single pole (SP) (2.6.1) of 'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for ection, testing and commissioning etc. as required single pole (SP) (2.6.1) by, Installation testing & commissioning of Main Switches (IS13940 part 3/1993) of following	Each Each Each Each Mtrs Mtrs Mtrs Mtrs Mtrs	2 1 1 2 7 58 90 85 85 72 75 8	212.9 260.2 318.89 360.83 473.49 125.05 126.07 140.03 157.41 188.49 45.83 130.16			42 26 314 72 3,314 7,252 11,346 11,902 13,379 13,571 3,437 1,041.
S/F ghti ssti JF ghti onn upp	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of dular base & cover in front including cutting the wall and making good the same in case of recessed 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 12 Modular box with base & cover 2x1.5+1x1.0 (1.8) 2x2.5+1x1.5 (1.8.1) 2x2.5+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.3) 2x6+1x2.5 (1.8.4) 1 Inverter wiring (1x1.5smm) Copper wire (1.19.1) ing and other loads in the existing MCB Distribution board ISI marked complete with connection, of 'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for ng and commissioning etc. as required single pole (SP) (2.6.1) of 'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for ection, testing and commissioning etc. as required single pole (SP) (2.6.1) by, Installation testing & commissioning of Main Switches (IS13940 part 3/1993) of following	Each Each Each Each Mtrs Mtrs Mtrs Mtrs Mtrs	2 1 1 2 7 58 90 85 85 72 75 8	212.9 260.2 318.89 360.83 473.49 125.05 126.07 140.03 157.41 188.49 45.83 130.16			42 26 31 72 3,314 7,252 11,346 11,902 13,379 13,571 3,437 1,041
S/F ghti ssti JF ghti onn upp	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of dular base & cover in front including cutting the wall and making good the same in case of recessed 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 6 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 2x1.5+1x1.0 (1.8) 2x1.5+1x1.0 (1.8) 2x1.5+1x1.0 (1.8) 2x4.5+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.3) 2x6+1x2.5 (1.8.4) 10 0 0 f 'B/C/D' series SP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for 19 mg and other loads in the existing MCB Distribution board ISI marked complete with connection. 10 f'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for 19 and other loads in the 2 Way double door MCB Distribution board ISI marked complete with connection. 19 MIN Installation teeting 4 commissioning etc. as required (2.6.2a)+(2.3.1b)	Each Each Each Each Mtrs Mtrs Mtrs Mtrs Mtrs	2 1 1 2 7 58 90 85 85 72 75 8	212.9 260.2 318.89 360.83 473.49 125.05 126.07 140.03 157.41 188.49 45.83 130.16			42 26 31 72 3,314 7,252 11,346 11,902 13,379 13,571 3,437 1,041
S/F co Win S/F ghti onn upp co ca)	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of dular base & cover in front including cutting the wall and making good the same in case of recessed and it as required. 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover 2x1.5+1x1.0 (1.8) 2x2.5+1x1.0 (1.8.1) 2x2.5+1x1.5 (1.8.1) 2x2.5+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.3) 2x6+1x2.5 (1.8.4) Inverter wiring (1x1.5smm) Copper wire (1.19.1) ing and other loads in the existing MCB Distribution board ISI marked complete with connection, 19 f 'B/C/D' series SP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for 19 and commissioning etc. as required single pole (SP) (2.6.1) 0 f 'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for 19 and commissioning etc. as required single pole (SP) (2.6.1) 0 f 'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for 19 and commissioning etc. as required single pole (SP) (2.6.1) 0 f 'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for 19 and other loads in the existing and commissioning etc. as required single pole (SP) (2.6.1) 0 f 'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for 19 and other loads in the 2 Way double door MCB Distribution board ISI marked complete with 19 y, Installation testing & commissioning etc. as required (2.6.2a)+(2.3.1b) 10 y, Installation testing & commissioning of Main Switches (IS13940 part 3/1993) of following acity on existing surface/wall mounting & complete with H.R.C fuse links, inter connections earthing s required as per direction of Engineer Incharge (Make-Seimens/HPL/Anchor/L&T /Havels/C&S/R.	Each Each Each Each Mtrs Mtrs Mtrs Mtrs Mtrs ach	2 1 1 2 7 58 90 85 85 72 75 8	212.9 260.2 318.89 360.83 473.49 125.05 126.07 140.03 157.41 188.49 45.83 130.16			42 26 314 72 3,314 7,252 11,346 11,902 13,379 13,571 3,437 1,041.
S/F co Wir S/F ghti onn upp co ca	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of dular base & cover in front including cutting the wall and making good the same in case of recessed 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 12 Modular box with base & cover 2x1.5+1x1.0 (1.8) 2x1.5+1x1.5 (1.8.1) 2x2.5+1x1.5 (1.8.1) 2x4+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.3) 2x6+1x2.5 (1.8.4) Inverter wiring (1x1.5smm) Copper wire (1.19.1) ing and other loads in the existing MCB Distribution board ISI marked complete with connection, ng and commissioning etc. as required single pole (SP) (2.6.1) of 'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for ection, testing and commissioning etc. as required single pole (SP) (2.6.1) of 'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for ection, testing and commissioning etc. as required (2.6.2a)+(2.3.1b) ing and other loads in the 2 Way double door MCB Distribution board ISI marked complete with ection, testing and commissioning etc. as required (2.6.2a)+(2.3.1b) ing and the loads in the 2 Way double door MCB Distribution board ISI marked complete with ection, testing and commissioning etc. as required (2.6.2a)+(2.3.1b) ing and the loads in the 2 Way double door MCB Distribution board ISI marked complete with ection etsting and commissioning etc. as required (2.6.2a)+(2.3.1b) ing with G.I. Earth pine 3 mtri long 4 complete with H.R.C fuse links, inter connections earthing s required as per direction of Engineer Incharge (Make-Seimens/HPL/Anchor/L&T /Havels/C&S/R. S/F of MCB 8 way Double door (2.3.6) to	Each Each Each Each Mtrs Mtrs Mtrs Mtrs Mtrs ach	2 1 1 2 7 58 90 85 85 72 75 8	212.9 260.2 318.89 360.83 473.49 125.05 126.07 140.03 157.41 188.49 45.83 130.16			1,17 42 260 318 721 3,314 7,252 11,346 11,902 13,379 13,571 3,437 1,041. 717.
S/ Ma co Wir S/F ghti onn upp oop c a)	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of dular base & cover in front including cutting the wall and making good the same in case of recessed 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 12 Modular box with base & cover 2x1.5+1x1.0 (1.8) 2x1.5+1x1.5 (1.8.1) 2x2.5+1x1.5 (1.8.1) 2x4+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.3) 2x6+1x2.5 (1.8.4) Inverter wiring (1x1.5smm) Copper wire (1.19.1) ing and other loads in the existing MCB Distribution board ISI marked complete with connection, ng and commissioning etc. as required single pole (SP) (2.6.1) of 'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for ection, testing and commissioning etc. as required single pole (SP) (2.6.1) of 'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for ection, testing and commissioning etc. as required (2.6.2a)+(2.3.1b) ing and other loads in the 2 Way double door MCB Distribution board ISI marked complete with ection, testing and commissioning etc. as required (2.6.2a)+(2.3.1b) ing and the loads in the 2 Way double door MCB Distribution board ISI marked complete with ection, testing and commissioning etc. as required (2.6.2a)+(2.3.1b) ing and the loads in the 2 Way double door MCB Distribution board ISI marked complete with ection etsting and commissioning etc. as required (2.6.2a)+(2.3.1b) ing with G.I. Earth pine 3 mtri long 4 complete with H.R.C fuse links, inter connections earthing s required as per direction of Engineer Incharge (Make-Seimens/HPL/Anchor/L&T /Havels/C&S/R. S/F of MCB 8 way Double door (2.3.6) to	Each Each Each Each Mtrs Mtrs Mtrs Mtrs Mtrs Mtrs Mtrs Mtrs	2 1 1 2 7 58 90 85 85 72 75 8 8 2 2	212.9 260.24 318.89 360.83 473.49 125.05 126.07 140.03 157.41 188.49 45.83 130.16 358.55			42 260 318 72 3,314 7,252 11,346 11,902 13,379 13,571 3,437 1,041. 717.
S/F co Wir S/F ghti onn upp oop c a) arth asc gui	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of dular base & cover in front including cutting the wall and making good the same in case of recessed 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 12 Modular box with base & cover 2x1.5+1x1.0 (1.8) 2x2.5+1x1.0 (1.8) 2x4.5+1x1.5 (1.8.1) 2x2.5+1x1.5 (1.8.4) 10 f 'B/C/D' series SP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for ng and other loads in the existing MCB Distribution board ISI marked complete with connection, of 'B/C/D' series SP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for ng and commissioning etc. as required single pole (SP) (2.6.1) of 'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for ng and commissioning etc. as required single pole (SP) (2.6.1) of 'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for ection, testing and commissioning of Main Switches (S13940 part 3/1993) of following acity on existing surface/wall mounting & complete with H.R.C fuse links, inter connections earthing acity on existing surface/wall mounting & complete with H.R.C fuse links, inter connections earthing s required as per direction of Engineer Incharge (Make-Seimens/HPL/Anchor/L&T /Havels/C&S/R. S/F of MCB 8 way Double door (2.3.6) Existing anary enclosure with cover plate having locking arrangement & watering pipe with charceal & self point ed (3.2)	Each Each Each Each Mtrs Mtrs Mtrs Mtrs Mtrs ach	2 1 1 2 7 58 90 85 85 72 75 8 8 2	212.9 260.24 318.89 360.83 473.49 125.05 126.07 140.03 157.41 188.49 45.83 130.16 358.55			42 260 318 721 3,314 7,252 11,346 11,902 13,379 13,571 3,437, 1,041. 717. 3,242,4
S/F co WVir S/F ghti onn upp co ca) arth asc gui	F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of dular base & cover in front including cutting the wall and making good the same in case of recessed 2 Modular box with base & cover 4 Modular box with base & cover 6 Modular box with base & cover 12 Modular box with base & cover 13 Modular box with base & cover 14 Modular box with base & cover 15 Modular box with base & cover 16 MC/D' series SP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for 19 and other loads in the 2 Way double door MCB Distribution board ISI marked complete with connection, esting and commissioning of Main Switches (S13940 part 3/1993) of following acity on existing surface/wall mounting & complete with H.R.C fuse links, inter connections earthing s required as per direction of Engineer Incharge (Make	Each Each Each Each Mtrs Mtrs Mtrs Mtrs Mtrs Mtrs Mtrs Mtrs	2 1 1 2 7 58 90 85 85 72 75 8 8 2 2	212.9 260.24 318.89 360.83 473.49 125.05 126.07 140.03 157.41 188.49 45.83 130.16 358.55			42: 260 318 721 3,314 7,252 11,346 11,902 13,379 13,571 3,437. 1,041.

Julion star

10 12. 10 m / 212 /

SI.					No.	
No.	Description of Items	Unit	Qnty	Rate		Amount
18	Providing & fixing plain 16/0.2mm twin twisted flexible, FR PVC insulated copper cable in polythene sleeve or conduit of suitable size on the floor/wall or side of the table/door etc as required.(1.31)	Mtrs	4	18.00		72.0
1 a j	Supply, Installation, Testing & Commissioning of exhaust fan upto 450 mm sweep in the exising opening, including making the hole to suit the size of the above fan making good the damaged complete, connection, etc as required. (1.43)	Each	2	1970.33		3,940.6
- 13	S/F of Call bell/Buzzer(Ding dong type) ISI marked suitable for DC/AC single phase 230 volts complete as required. (1.30)	Each	1	120.00		120.0
	S/F of 18-25Watt L.E.D Tube light fitting with all accessories and connections (Make:HPL-Neptune Havells-Elite LED Pride Plus/PAC/Crompton-RetroPLL	Each	14	683.00		9,562.00
22	Supply of 1200mm A.C. Ceiling fan with all accessories and connections with out fan regulator (Make:Usha-Striker Millenium/Crompton-Jura /Anchor-XL/Havels-Velocity/Spark/Orient-Summer pride)	Each	7	2425.00		16,975.00
23	S/F step type fan regulator	Each	7	377.00		2,639.00
	Supply & fixing of superior type C.I bulk head fitting with 9W Led Bulb for general domestic use ISI marked square / oval type with premetallic glass cover provided with galvanized steel wire guard including necessary connections. (M-5)	Each	1	587.00		587.00
	Supply & Fixing of 20-25Watt single L.E.D street light fitting with LED & Electrinic driver including all accessories and connections (Make:Crompton/Phillips/HPL/Polycab/Havells)	Each	1	2878.00		2,878.00
	Supply & Fixing of 30-35Watt single L.E.D street light fitting with LED & Electrinic driver including all accessories and connections (Make:Crompton/Phillips/HPL/Polycab/Havells)	Each	1	3402.00		3,402.00
	Supply & Fixing of 45-48 Watt single L.E.D street light fitting with LED & Electrinic driver including all accessories and connections (Make:Crompton/Phillips/HPL/Polycab/Havells)	Each	1	5706.00		5,706.00
28	S/F of electronic 9w Watt LED Bulb	Each	12	169.65		2,035.80
		Each	7	241.00		1,687.00
	S/F of 6 sqmm twin core unbonded aluminium service connection wire with no.10 G.I. Guard wire to support the aluminium wire	Mtrs	45	42.00		1,890.00
		Each	1	17024.00		17,024.00
	Provision of 40mm dia HDPE pipe for laying & protection of cable	Mtrs		120.00		
	S/F of Main incoming switch box i) 63A DP MCCB-1 no ii) 63A DP RCCB- 1no iii) 275V,20KA SPD 1no iv) 63A Bus bar	LS	1	15408.00	0	15,408.00
			5	TOTAL		197,352.04
				Say RS		197352.00

an Bolin 25 m strang

20

1.7

Side on her