Tender Inviting Autority: CDM & PHO Kandhamal.

NAME OF THE PROJECT:- CONSTRUCTION OF DAY CARE SUBCENTRE - CUM - HEALTH & WELLNESS CENTRE AT PHIRINGIA M.C. UNDER CHAKAPADA BLOCK OF KANDHAMAL DISTRICT FOR THE YEAR 2021-22

Amount put to tender Rs. 2.368.037.00

SCHEDULE OF WORKS SI Description of work Unit **Estimated Rate** AMOUNT No.or No. Qty. Figure Words Rs. CIVIL WORK Earth work in excavation of foundation in hard or gravel soil with initial lead and lifts including dressing and leveling the bed and depositing the excavated earth at places away from work site with all leads and lifts including cost of all labour, cess and T&P and dewatering if required for the work etc. Complete as directed by the Engineerin charge 1.01 Ground Floor 69.51 Cum 188.77 13121.40 Supplying & filling good clean river sand inside the foundation / plinth of approved area including watering to complete saturation & ramming complete with all leads & lifts including cost, 2 conveyance, royalty, cess & taxes of all materials & cost of all labour & T&P required for the work complete (measurement will be taken for compacted section) as per direction of Engineer-in-Charge. 2.01 Ground Floor 57.16 One Cum 948.24 54201.40 Cement Concrete of proportion (1:3:6) in foundation and floors using 4cm size clean hard 3 black broken granite stone metal of approved quality and from approved quarry including hosting lowering and laying concrete in layers not 3.01 17.94 One Cum 5163.88 92640.01 RCC of design mix of M-20 grade of controlled qulity having cube strength of 250kg./cm2 in design mix with minimum quantity of cement as specified in IRC Code of 150 mm. cubes at 28 days curing after mixing & tests conducted in accordance with relevant clauses of IS 456/IS 516/IRC 16/1987/IRC-78/1983 using crusher 4 broken hard granite course aggregate of 10 mm. to 20mm. sizes & proportion as specified in clause-302.6.2 of IRC 21/1987, IS-10262 & subject to mix design in conformity with the grading & proportion of different materials for concrete as specified in the relevant codes of approved Column Base & Grade Beam (Ground Floor) 4.01 12.94 One Cum 5905.89 76422.22 4.02 Column in Super structure (Ground Floor) 6.41 One Cum 13079.58 83840.11 4.03 column First Floor 1.63 One Cum 14628.44 23844.36 Plinth Band/Grade Beam 4.04 3.68 One Cum 6260.91 23040.15 4.05 Lintel (Ground Floor) 2.49 One Cum 9441.60 23509.58 Wall Beam & T-Beams(Ground Floor) 4.06 5.34 One Cum 13079.58 69844.96 4.07 Roof Beam First Floor 0.77 One Cum 14628.44 11263.90 4.08 Chajja & fins (Ground Floor) 3.03 One Cum 845.08 2560.59 4.09 Chhaja First Floor 7.02 One Cum 944.74 6632.07 Stair case (Ground Floor) 4.1 1.53 One Cum 11133.11 17033.66 4.11 Roof Slab (Ground Floor) 7.99 One Cum 10036.45 80191.24 4.12 First Floor Slab 1.84 One Cum 10976.69

20197.11

13ch 2-12-21

	0.0				
10.01	Ground Froor	30.20	1		
10 01	on 20 mm thick cement mortar (1:4) and filling joints with white cement of approved quality including cost of all materials, etc. required for the work all complete as per direction of E.I.C. Ground Floor	88.20	One Sqm	985.69	 86937.86
	Supplying, fitting and fixing Vitrified tile in floors of approved make conformaing to IS:13755 laid				
9.02	First Floor	21.92	One Sqm	218.55	4790.62
9.01	of all labour, etc complete as per the direction of E.I.C. Ground Floor	507.47	One Sqm		108431.11
9	16mm thick C.P. (1:6) over brick masonary to the smooth surface including watering, curing cost, carriage, royalty, and taxes of all materials, cost	y .			
8.02	First Floor	59.06	One Sqm	157.38	9294.86
8.01	floors as per direction of the Engineer in charge. Ground Floor	141.97	One Sqm		21565.24
8	12mm thick cement plaster (1:4) over brick work including cement punning and Bitumen painting on top including, watering and curing with cost and conveyance of all materials and labour, cess with T&P required for the work with all taxes and royalties, Cess etc. complete in all respect in all				
7.02	First Floor	9.15	One Cum	4,761.24	43565.35
7.01	taxes of all materials, cost of all labour, etc complete as per the direction of E.I.C. (in Super Structure) Ground Floor	37.38	One Cum	4,496.36	168073.94
7	8cm size having crushing strength not less than 75Kg/cm2 with dimensional tolerance ±2 percent in cement mortar (1:6) in Foundation including watering curing, cost of carriage, royalty and				76.1 10.5.2
6.01	Ground Floor Brick work with Flyash Bricks 25cm x 12cm x	19.31	One Cum	3,984.20	70304.30
6	Brick work with Flyash Bricks 25cm x 12cm x 8cm size having crushing strength not less than 75Kg/cm2 with dimensional tolerance ±2 percent in cement mortar (1:6) in Foundation including watering curing, cost of carriage, royalty and taxes of all materials, cost of all labour, etc complete as per the direction of E.I.C.	10.04	One Cum	2 084 20	76934.90
5.02	First Floor	5.67	One Qtl	8,956.66	50784.26
5.01	Ground Floor	43.41	One QtI	8,933.04	387783.27
5	grade cutting bending , binding, lapping, splicing, welding etc. (conforming to ISI specification) & jointing if necessary by lapping & tying the grills & placing in position as required for RCC works as per the approved design, hoisting, lowering & laying position including cost & conveyance, Cess of tor steel & binding wires of 18 to 20 gauge (as approved by the Deptt.) etc. complete (Weight of binding wire shall not be considered for payment at all which will be bome by the contractor (standard CO-efficient of different size of the steel shall be considered & welding & lapping should confirm to relevant clause of IRC - 21/1987) as per direction of the Engineer in charge.				

Dax is

	Fixing tiles in dados skirting and risers of steps on 12mm thick CP (1:3) jointed with neat cement					
11	slurry mixed with pigments to match the shade of					
	the tiles including cost, carriage, cost of all	y x F				
	labour etc. complete.		lance.			
11.01	Ground Floor	53.25	One Sqm	1,033.73		55046.12
1000	Priming 1 coat with wall primer water bond					
12	cement primer including all labour, materials etc.	1.				
12.01	complete. Ground Floor	500.40	-			
12.01		596.19	One Sqm	58.51		34883.08
12.02	First Floor	59.06	One Sqm	60.94	-	3599.12
12.03	Wall pointing 2 poots with plactic and lain a sixt	21.92	One Sqm	59.97		1314.54
13	Wall painting 2 coats with plastic emulsion paint of approved shade on new work to give an even shade including cost of paint etc complete.					
13.01	Ground Floor	454.22	One Sqm	77.33		35124.83
13.02	First Floor	21.92	One Sqm	78.90		1729.49
10.02	Wall painting two coat with any approved	21.02	One Sqiii	70.90		1729.49
14	weather coat paint including cost of all materials, labour and T&P require for the work etc. complete as directed by the E.I.C.	11 22				
14.01	Ground Floor	141.97	One Sqm	71.07		10089.81
14.02	First Floor	59.06	One Sam	73.67		4350.83
	Supplying of M.S. Door, Window with grills, Grills		- 54	. 5.51		.000.00
	made out of M.S. Angle frame, M.S. Flat, Sheet			1 1		
	etc of approved section & design, electrically					
15	welded properly with all necessary locking			5		
	arrengement, and 1 coat red oxide primer			e a a		
	including cost of all materials, labour charges,			-		
200	carriage of materials to site etc. complete.				75 E	
15.01	Ground Floor	155.40	ka	76.15	-	44000 74
15.02	Ground Floor	257.00	kg	80.29		11833.71
15.03	First Floor	236.40	kg	76.15		20634.53
10.00	Supplying, fitting and fixing of stainless steel of	230.40	kg	70.15		18001.86
	304 grade in hand railing using 50 mm dia of 2			7 7		
	mm thick circular pipe with Balustrade of size 32					
	mm x 32mm x 2mm @ 0.90 mtr C/C and					
16	stainless aquare pipe bracing of size case as per		.= =			
	approved design and specification, buffing,		2			
	polishing etc. with the cost, conveyance taxses					
	of all material, cost of all labour etc. complete in					
16.01	all respect. Ground Floor	4.50				
10.01	Supplying and fitting-fixng of Un-plasticised Poly	4.50	Rmt	3,682.09		16569.41
	Vinyl Chloride (UPVC) (FENESTA/ NCL VERA					
	LTD Casement Door - 60- Series duly		a 17 17 180			
	manufactured using UPVC reinforeced profiles of					
	60mm x 55 mm x 25 mm for outer frames, 102					
	mm x 80 mm for casement Door Sash Profle and				-	
	74 mm x 60 mmx2 5mm mullion profile capable				, a	
	of mounting single glazing system structurally			. a		
	reinforced with hot dip galvanised up to 50					
	microns of minimum thickness of 2.0 mm		-		-	
	prefabricated & welded through fusion welding		-			
	the door each shall be fited with 12mm thick		1 1			
	the door sash shall be fited with 12mm thick WPC Board of Greenply make duly fixed with		> ,	W.		
17	the door sash shall be fited with 12mm thick WPC Board of Greenply make duly fixed with EPDM weathering seal resistant accessories like			2		
17	WPC Board of Greenply make duly fixed with EPDM weathering seal resistant accessories like cliping locking system made of aluminium 1 No		2 , sar = ;	2 2 11		
17	WPC Board of Greenply make duly fixed with EPDM weathering seal resistant accessories like cliping locking system made of aluminium 1 No per set of sashes and the system is to be	Sec. 1				
17	WPC Board of Greenply make duly fixed with EPDM weathering seal resistant accessories like cliping locking system made of aluminium 1 No per set of sashes and the system is to be installed at the side using anchor fasteners,	Mr. I				
17	WPC Board of Greenply make duly fixed with EPDM weathering seal resistant accessories like cliping locking system made of aluminium 1 No per set of sashes and the system is to be installed at the side using anchor fasteners, silicone rubber sealant, easy glazing / deglazing		2 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4		Y	
17	WPC Board of Greenply make duly fixed with EPDM weathering seal resistant accessories like cliping locking system made of aluminium 1 No per set of sashes and the system is to be installed at the side using anchor fasteners, silicone rubber sealant, easy glazing / deglazing at side etc.including cost andconveyance of all					
17	WPC Board of Greenply make duly fixed with EPDM weathering seal resistant accessories like cliping locking system made of aluminium 1 No per set of sashes and the system is to be installed at the side using anchor fasteners, silicone rubber sealant, easy glazing / deglazing at side etc.including cost andconveyance of all materials conforming to ASTM D 638-421477-95	Jan 1				
17	WPC Board of Greenply make duly fixed with EPDM weathering seal resistant accessories like cliping locking system made of aluminium 1 No per set of sashes and the system is to be installed at the side using anchor fasteners, silicone rubber sealant, easy glazing / deglazing at side etc.including cost andconveyance of all materials conforming to ASTM D 638-421477-95 and the applicable codes and standards.As per	Jan 1		A		
17	WPC Board of Greenply make duly fixed with EPDM weathering seal resistant accessories like cliping locking system made of aluminium 1 No per set of sashes and the system is to be installed at the side using anchor fasteners, silicone rubber sealant, easy glazing / deglazing at side etc.including cost andconveyance of all materials conforming to ASTM D 638-421477-95 and the applicable codes and standards.As per specification approved by the Department & as	Jan !		A		
17	WPC Board of Greenply make duly fixed with EPDM weathering seal resistant accessories like cliping locking system made of aluminium 1 No per set of sashes and the system is to be installed at the side using anchor fasteners, silicone rubber sealant, easy glazing / deglazing at side etc.including cost andconveyance of all materials conforming to ASTM D 638-421477-95 and the applicable codes and standards.As per	Jan !				
17	WPC Board of Greenply make duly fixed with EPDM weathering seal resistant accessories like cliping locking system made of aluminium 1 No per set of sashes and the system is to be installed at the side using anchor fasteners, silicone rubber sealant, easy glazing / deglazing at side etc.including cost andconveyance of all materials conforming to ASTM D 638-421477-95 and the applicable codes and standards.As per specification approved by the Department & as per derection of the E.I.C. SE No 16100 dt					
17	WPC Board of Greenply make duly fixed with EPDM weathering seal resistant accessories like cliping locking system made of aluminium 1 No per set of sashes and the system is to be installed at the side using anchor fasteners, silicone rubber sealant, easy glazing / deglazing at side etc.including cost andconveyance of all materials conforming to ASTM D 638-421477-95 and the applicable codes and standards.As per specification approved by the Department & as per derection of the E.I.C. SE No 16100 dt					

my gh

KO TO THE TOTAL PROPERTY OF THE PROPERTY OF TH



			ТО	TAL		2368037.00
				VORK		197282.00
				VORK		196601.00
otal estima	ated cost in Figures			WORK	1	1974154.00
atal aati	that and in Fi					1974154.06
21	Branding	80.00	One Sqm	40.00		3200.00
20.02	First Floor	14.71	One Sqm	351.89		5176.30
20.01	Ground Floor	98.13	One Sqm	324.03		31797.06
20	25mm thick CC 1:2:2 with 6mm size CB chips for grading concret over roof slab etc. complete.					
19.02	First Floor	7.88	One Sqm	135.06		1064.27
19.01	Ground Floor	18.03	One Sqm	135.06		2435.13
19	Painting two coats with approved enamel paints of approved colour, shade over a coat of primer including sand papering, polishing the surface, cost, conveyances of all materials and cost of all labour etc, complete as per specification & direction of E.I.C.				-	
18.01	including all fitting includingcost of materials all taxes labour, T&P etc. complete as per direction of Engineer-incharge.	8.75	One Sqm	5,767.46	3.	50465.28
18	Supplying, fitting, fixing up window (sliding type) made up aluminum Section 151-154, 151-155, as windows frame section No. 151- 155, 151-153 and 151-167 as shutter frame with 5mm thick black glass as panel fitted with rubber beading including locking arrangement					

(Rupees Twenty three lakh sixty eight thousand thirty seven only)

Mehal 12 202

CDM & BHO Kandhamal

My Quoted rate isto the Estimated Cost

% (Both in Figure and words) excessover/ Less than/ Equal to

Signature of the Contractor

Notes:

(1) The contractor should not write any thing except quoting of percentage and in case anything else regarding tender rate is mentioned, the tender is liable for rejection.

(2) Strike out which are not applicable.

(m) who

Ro-

Zalz well

9/2:12

phinisa Mc

	PH WORK	*			
SI No	Description of items	Qty	Unit	Rate	Amount
1	Supplying all materials, labour, T&P and providing and fixing to wall or ceiling and floor IS marked galvanised mild steel tubes (medium grade) confirming to IS: 1239/1990, part-1 of the following nominal bore, tube fittings and clamps including making good the wall, ceiling and floor, testing all complete as per specification and direction of the Engineer in			nate	Amount
	charge				
	in Ground Floor			10.00	1,
a	25 mm dia G.I pipe	6.00	Mtr	294.40	1766.4
b	32 mm dia G.I pipe in First Floor	6.00	Mtr	362.10	2172.6
a	25 mm dia G.I pipe	0.00	ļ.,.	200.00	
b	32 mm dia G.I pipe		Mtr	298.60	2388.8
c	32 mm dia G.I pipe	11.00		366.90 372.40	3302.1 4096.4
d	40 mm dia G.I pipe (For inter Connection)	11.50		450.90	5185.3
2	Supplying all materials, labour, T&P and providing and fixing to wall or ceiling and floor C-pc pipes and pipe fittings of the following nominal borewith clamps including making good the wall testing all complete as per specification and direction of the Engineer in charge	tur e			
	In ground floor				
a	20 mm C-PVC pipes	6.00	Mtr	198.30	1189.8
b	25mm C-PVC pipes	9.00	Mtr	276.20	2485.8
a	in First Floor 20 mm C-PVC pipes				
b	25mm C-PVC pipes	6.00		203.50	1221.0
3	supplying all materials, labour, T&P and cutting holes through existing	8.00	Mtr	281.40	2251.2
	brick work including making good the damages in cement mortar (1:4) for taking G.I. Pipes and fittings/ P.V.C. pipes and fittings etc. all complete as per P.H. specification and direction of E.I.C				
a	250 mm thick wall in GF	6.00	Each	32.20	193.2
b 4	251 mm thick wall in GF	3.00	Each	32.80	98.4
7	supplying all materials, labour, T&P and cutting holes in R.C.C. floors, roofs, erc. up to 19 Cm. thick for passing G.i. Pipes and fittings/ P.V.C. pipes and fittings etc. and reparing the holes after insertion of pipes etc. with cement concrete (1:2:4) including finishing complete so as to make it leak proof as per direction of E.I.C.				
5	In ground floor	3.00	Each	104.00	312.00
3	Supplying all materials, labour, T&P and cutting grooves in pucca floors and walls for taking G.I./P.V.C. pipes and making good the damages as per direction of the E.I.C.		v **		
	In ground floor	6.00	Mtr	131.10	786.60
6	Supplying all materials, labour T&P and fitting and fixing brass/CP fittings of the following nominal bore with supply of all joiniting materials complete as per specification and direction of the Engineer in charge	e e			
а	15mm dia Cp Long body bib cock jaquar make)	5.00	Fach	875.30	4376.50
b	15mm dia CP angle stop cock (jaquar make)	5.00		612.70	3063.50
С	20mm dia CP concealed stop cock (jaquar make)	2.00		919.00	1838.00
d	25mm dia brass or gun metal full way valve(shaktimake)	3.00		909.90	2729.70
e	32 mm dia brass or gun metal full way valve(shakti make)	2.00		1331.40	2662.80
	15mm dia CP Flange	5.00		40.30	201.50
7	15mm dia CP Extention Nipple Supplying all materials, labour, T&P and 67 with 15mm or 20mm inlet fitting and fixing CP shower specification and direction of the including Engineer polishing in charge all complete as per	6.00	Each	59.30	355.80
	15mm dia CP revolving shower with 15mm x 225mm a shower arm long size CP Shower Arm	2.00		458.30	916.60

Ou m

D'Y. N.

	Supplying an materials, labour, T&P and Fixing Rosestand A	•			
	Supplying all materials, labour, T&P and Fixing Rotational Moulded Polyethelene cylindrical water stroage tanks conforming to IS 12701-1996 including cutting holes through the state of th				
	and providing extra socket and iam Nuts. First and fixing miled steel tubes and fittings				1
	and providing extra socket and jam Nuts, Fixing Valves etc, including hoisting upto a height of 5 mtr above ground leads				1
	upto a height of 5 mtr above ground level and placing the tank to the required position and providing			1.	1
9	1000 litre capacity water storage tanks on roof of SF(without staging)	1.0	0 Each		
9	a priving son waste ventilating all materials pines labour 1 ft.	1.0	UlEach	8711.30	0 87
	did living and living full side H-DV/C diameter City				
	comorning to ISI NO 13592/1992 to walls with noils balls.		1		ŀ
	wooden plugs or laying in trenches including jointing with supply of	1			
	approved rubber lubricant by non-heat application method/as per				
	manufacturer's specification, testing, earthwork in excavation in all		1		
	kinds of soil and refilling of trenches as per specification and direction				1
	of the engineer in charge			1	
		-	1		
	110mm diameter II DVG CNVD		-		1
	110mm diameter U-PVC SWR pipes(Supreme/Ashirvad)	9.00	Mtr	204.20	
	75mm diameter U-PVC SWR pipes(Supreme/Ashirvad)		Mtr	284.20	
	110mm U-PVC door Tee			153.70	
	110mm U-PVC offset		Each	137.20	41
	110mm U-PVC door bend		Each	115.20	34.
	110mm U-PVC plain shoe bend		Each	131.70	790
	110mm U-PVC cowl		Each	186.50	373
	110mm P-trap	2.00	Each	38.40	76
	75mm U-PVC plain Tee		Each	225.00	
	75mm U-PVC plain bend	1.00		65.90	225
10	Supplying all materials labour TOD	3.00			65
	Supplying all materials, labour T&P and cutting holels through existing		Lucii	49.40	148
12	The mason y wall for taking H C I pings and the				
	o o duiliages ett. dii complete ac par bit c			1 1	
	and direction of the Engineer in charge			1 1	
	250mm to 375mm thick wall				
44					
11	Supplying all materials, labour T&P and and fixing 10 liters canacity.	6.00	ach	136.50	819
11	Supplying all materials, labour T&P and and fixing 10 liters capacity low level flushing cistern with a pair of cast iron or M.S. breakets	6.00	ach	136.50	819.
11	with fittings such as siphonic arrangements 15	6.00	ach	136.50	819.
11	with fittings such as siphonic arrangements 15	6.00	ach	136.50	819.
11	with fittings such as siphonic arrangements 15mm nominal size prass/pvc ball valve with polythene float CD brass/	6.00	ach	136.50	819.
11	with fittings such as siphonic arrangements 15mm nominal size orass/pvc ball valve with polythene float CP brass handle, unions and Couplings for connection with inlet, outlook and arrangements.	6.00	ach	136.50	819.
11	with fittings such as siphonic arrangements 15mm nominal size brass/pvc ball valve with polythene float CP brass handle,unions and Couplings for connection with inlet, outlet and overflow pipes, 32mm dia	6.00	Each	136.50	819.
	with fittings such as siphonic arrangements 15mm nominal size brass/pvc ball valve with polythene float CP brass handle,unions and Couplings for connection with inlet, outlet and overflow pipes, 32mm dia Cp Long flush bend, 15mm dia pvc inlet connection pipe including	6.00	Each	136.50	819.
11	with fittings such as siphonic arrangements 15mm nominal size brass/pvc ball valve with polythene float CP brass handle,unions and Couplings for connection with inlet, outlet and overflow pipes, 32mm dia Cp Long flush bend, 15mm dia pvc inlet connection pipe including cutting holes and making good the same and connecting the flush bend with cistren and closet and connecting the inlet pipe.	6.00	ach	136.50	819.
	with fittings such as siphonic arrangements 15mm nominal size brass/pvc ball valve with polythene float CP brass handle,unions and Couplings for connection with inlet, outlet and overflow pipes, 32mm dia Cp Long flush bend, 15mm dia pvc inlet connection pipe including cutting holes and making good the same and connecting the flush bend with cistren and closet and connecting the inlet pipe with suupply main etc all complete as per the specification and direction of the Facilies.	6.00	ach	136.50	819.
	with fittings such as siphonic arrangements 15mm nominal size brass/pvc ball valve with polythene float CP brass handle,unions and Couplings for connection with inlet, outlet and overflow pipes, 32mm dia Cp Long flush bend, 15mm dia pvc inlet connection pipe including	6.00	ach	136.50	819.
	with fittings such as siphonic arrangements 15mm nominal size brass/pvc ball valve with polythene float CP brass handle,unions and Couplings for connection with inlet, outlet and overflow pipes, 32mm dia Cp Long flush bend, 15mm dia pvc inlet connection pipe including cutting holes and making good the same and connecting the flush bend with cistren and closet and connecting the inlet pipe with suupply main etc all complete as per the specification and direction of the Facilies.	6.00	ach	136.50	819.
	with fittings such as siphonic arrangements 15mm nominal size brass/pvc ball valve with polythene float CP brass handle,unions and Couplings for connection with inlet, outlet and overflow pipes, 32mm dia Cp Long flush bend, 15mm dia pvc inlet connection pipe including cutting holes and making good the same and connecting the flush bend with cistren and closet and connecting the inlet pipe with suupply main etc all complete as per the specification and direction of the Facilies.	6.00	ach	136.50	819.
	with fittings such as siphonic arrangements 15mm nominal size brass/pvc ball valve with polythene float CP brass handle,unions and Couplings for connection with inlet, outlet and overflow pipes, 32mm dia Cp Long flush bend, 15mm dia pvc inlet connection pipe including cutting holes and making good the same and connecting the flush bend with cistren and closet and connecting the inlet pipe with suupply main etc all complete as per the specification and direction of the Facilies.	6.00	Each	136.50	819.
11	with fittings such as siphonic arrangements 15mm nominal size brass/pvc ball valve with polythene float CP brass handle, unions and Couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including cutting holes and making good the same and connecting the flush bend with cistren and closet and connceting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in	6.00	Each	136.50	819.
11	with fittings such as siphonic arrangements 15mm nominal size crass/pvc ball valve with polythene float CP brass handle, unions and couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including cutting holes and making good the same and connecting the flush bend with cistren and closet and connceting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in the coupling couplings.	6.00	Each	136.50	819.
11	with fittings such as siphonic arrangements 15mm nominal size brass/pvc ball valve with polythene float CP brass handle, unions and couplings for connection with inlet, outlet and overflow pipes, 32mm dia cp Long flush bend, 15mm dia pvc inlet connection pipe including cutting holes and making good the same and connecting the flush bend with cistren and closet and connecting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in collitres Capacity PVC cistren with 32mm dia flush bend carryware/Hindware/Neycer/Rak)				819.
11	with fittings such as siphonic arrangements 15mm nominal size brass/pvc ball valve with polythene float CP brass handle, unions and couplings for connection with inlet, outlet and overflow pipes, 32mm dia Ep Long flush bend, 15mm dia pvc inlet connection pipe including cutting holes and making good the same and connecting the flush bend with cistren and closet and connceting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in considerable bend carryware/Hindware/Neycer/Rak) complying all materials, labour. T&P and fixing with the sum of the su	2.00 Ea		136.50	
11	with fittings such as siphonic arrangements 15mm nominal size brass/pvc ball valve with polythene float CP brass handle, unions and couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including sutting holes and making good the same and connecting the flush bend with cistren and closet and connecting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in harge Ditres Capacity PVC cistren with 32mm dia flush bend carryware/Hindware/Neycer/Rak) Applying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C. pag/Oriene)				
11	with fittings such as siphonic arrangements 15mm nominal size orass/pvc ball valve with polythene float CP brass handle, unions and couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including outling holes and making good the same and connecting the flush bend with cistren and closet and connecting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in harge O litres Capacity PVC cistren with 32mm dia flush bend carryware/Hindware/Neycer/Rak) Applying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C pan/Orissa pattern squatting an) duly embedded in cement concert (15 f. 16).				
11	with fittings such as siphonic arrangements 15mm nominal size orass/pvc ball valve with polythene float CP brass handle, unions and couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including outling holes and making good the same and connecting the flush bend with cistren and closet and connecting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in harge O litres Capacity PVC cistren with 32mm dia flush bend carryware/Hindware/Neycer/Rak) Applying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C pan/Orissa pattern squatting an) duly embedded in cement concert (15 f. 16).				
11 CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC	with fittings such as siphonic arrangements 15mm nominal size orass/pvc ball valve with polythene float CP brass handle, unions and couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including outling holes and making good the same and connecting the flush bend with cistren and closet and connecting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in harge O litres Capacity PVC cistren with 32mm dia flush bend carryware/Hindware/Neycer/Rak) Applying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C pan/Orissa pattern squatting and outly embedded in cement concrete (1:5:10) using 4cm size hard anite metal including fixing a pair of vitreous china water specification.				
11 (C)	with fittings such as siphonic arrangements 15mm nominal size brass/pvc ball valve with polythene float CP brass handle, unions and couplings for connection with inlet, outlet and overflow pipes, 32mm dia Ep Long flush bend, 15mm dia pvc inlet connection pipe including sutting holes and making good the same and connecting the flush bend with cistren and closet and connecting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in harge Ditres Capacity PVC cistren with 32mm dia flush bend carryware/Hindware/Neycer/Rak) Applying all materials, labour, T&P and fixing vitreous china water coset, squattingpan (Indian type W.C pan/Orissa pattern squatting and outly embedded in cement concrete (1:5:10) using 4cm size hard anite metal including fixing a pair of vitreous china 250mm x 130mm flootrest, fixing 100mm dia HCI in color in the control of the control of the color of the control of the color of the c				
11 CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC	with fittings such as siphonic arrangements 15mm nominal size orass/pvc ball valve with polythene float CP brass handle, unions and couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including rutting holes and making good the same and connecting the flush bend with cistren and closet and connecting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in harge Ditres Capacity PVC cistren with 32mm dia flush bend carryware/Hindware/Neycer/Rak) Applying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C pan/Orissa pattern squatting and outly embedded in cement concrete (1:5:10) using 4cm size hard anite metal including fixing a pair of vitreous china 250mm x 130mm flootrest, fixing 100mm dia HCl 'p' or 's' trap (with/without 50mm a horn) for water colset squatting nan including titing the limitation of the control of the contr				
11 C C C C C C C C C C C C C C C C C C	with fittings such as siphonic arrangements 15mm nominal size orass/pvc ball valve with polythene float CP brass handle, unions and couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including rutting holes and making good the same and connecting the flush bend with cistren and closet and connceting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in harge Ditres Capacity PVC cistren with 32mm dia flush bend carryware/Hindware/Neycer/Rak) Applying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C pan/Orissa pattern squatting and outly embedded in cement concrete (1:5:10) using 4cm size hard anite metal including fixing a pair of vitreous china 250mm x 130mm footrest, fixing 100mm dia HCl 'p' or 's' trap (with/without 50mm a horn) for water colset squatting pan including jointing the trap with in in cement mortar (1:1) cutting the floor and mendia.				
11 CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC	with fittings such as siphonic arrangements 15mm nominal size orass/pvc ball valve with polythene float CP brass handle, unions and couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including rutting holes and making good the same and connecting the flush bend with cistren and closet and connceting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in harge Ditres Capacity PVC cistren with 32mm dia flush bend carryware/Hindware/Neycer/Rak) Applying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C pan/Orissa pattern squatting and outly embedded in cement concrete (1:5:10) using 4cm size hard anite metal including fixing a pair of vitreous china 250mm x 130mm 0mm footrest, fixing 100mm dia HCl 'p' or 's' trap (with/without 50mm a horn) for water colset squatting pan including jointing the trap with in in cement mortar (1:1) cutting the floor and mending good the mages etc all complete as per specification and direction.				
11 CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC	with fittings such as siphonic arrangements 15mm nominal size orass/pvc ball valve with polythene float CP brass handle, unions and couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including rutting holes and making good the same and connecting the flush bend with cistren and closet and connecting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in harge Ditres Capacity PVC cistren with 32mm dia flush bend carryware/Hindware/Neycer/Rak) Applying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C pan/Orissa pattern squatting and outly embedded in cement concrete (1:5:10) using 4cm size hard anite metal including fixing a pair of vitreous china 250mm x 130mm flootrest, fixing 100mm dia HCl 'p' or 's' trap (with/without 50mm a horn) for water colset squatting nan including titing the limitation of the control of the contr				
11 (C)	with fittings such as siphonic arrangements 15mm nominal size orass/pvc ball valve with polythene float CP brass handle, unions and couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including rutting holes and making good the same and connecting the flush bend with cistren and closet and connceting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in harge Ditres Capacity PVC cistren with 32mm dia flush bend carryware/Hindware/Neycer/Rak) Applying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C pan/Orissa pattern squatting and outly embedded in cement concrete (1:5:10) using 4cm size hard anite metal including fixing a pair of vitreous china 250mm x 130mm footrest, fixing 100mm dia HCl 'p' or 's' trap (with/without 50mm a horn) for water colset squatting pan including jointing the trap with in in cement mortar (1:1) cutting the floor and mending good the mages etc all complete as per specification and direction of the gineer in charge				
11 (C)	with fittings such as siphonic arrangements 15mm nominal size orass/pvc ball valve with polythene float CP brass handle, unions and couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including rutting holes and making good the same and connecting the flush bend with cistren and closet and connceting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in harge Ditres Capacity PVC cistren with 32mm dia flush bend carryware/Hindware/Neycer/Rak) Applying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C pan/Orissa pattern squatting and outly embedded in cement concrete (1:5:10) using 4cm size hard anite metal including fixing a pair of vitreous china 250mm x 130mm footrest, fixing 100mm dia HCl 'p' or 's' trap (with/without 50mm a horn) for water colset squatting pan including jointing the trap with in in cement mortar (1:1) cutting the floor and mending good the mages etc all complete as per specification and direction of the gineer in charge				
11 (C)	with fittings such as siphonic arrangements 15mm nominal size orass/pvc ball valve with polythene float CP brass handle, unions and couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including rutting holes and making good the same and connecting the flush bend with cistren and closet and connceting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in harge Ditres Capacity PVC cistren with 32mm dia flush bend carryware/Hindware/Neycer/Rak) Applying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C pan/Orissa pattern squatting and only embedded in cement concrete (1:5:10) using 4cm size hard anite metal including fixing a pair of vitreous china 250mm x 130mm footrest, fixing 100mm dia HCl 'p' or 's' trap (with/without 50mm a horn) for water colset squatting pan including jointing the trap with in in cement mortar (1:1) cutting the floor and mending good the mages etc all complete as per specification and direction of the gineer in charge	2.00 Ea	ch	1279.90	2559.8
11 (C)	with fittings such as siphonic arrangements 15mm nominal size orass/pvc ball valve with polythene float CP brass handle, unions and couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including rutting holes and making good the same and connecting the flush bend with cistren and closet and connceting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in harge Ditres Capacity PVC cistren with 32mm dia flush bend carryware/Hindware/Neycer/Rak) Applying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C pan/Orissa pattern squatting and only embedded in cement concrete (1:5:10) using 4cm size hard anite metal including fixing a pair of vitreous china 250mm x 130mm footrest, fixing 100mm dia HCl 'p' or 's' trap (with/without 50mm a horn) for water colset squatting pan including jointing the trap with in in cement mortar (1:1) cutting the floor and mending good the mages etc all complete as per specification and direction of the gineer in charge Domm size Orissa pan(Parryware/Hindware/Neycer/Rak) Doplying all materials, labour, T&P and fixing the filter in the		ch		
11 (GC) (CC) (FC) (FC) (FC) (FC) (FC) (FC) (F	with fittings such as siphonic arrangements 15mm nominal size orass/pvc ball valve with polythene float CP brass handle, unions and couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including rutting holes and making good the same and connecting the flush bend with cistren and closet and connceting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in harge O litres Capacity PVC cistren with 32mm dia flush bend carryware/Hindware/Neycer/Rak) Applying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C pan/Orissa pattern squatting and only embedded in cement concrete (1:5:10) using 4cm size hard anite metal including fixing a pair of vitreous china 250mm x 130mm footrest, fixing 100mm dia HCl 'p' or 's' trap (with/without 50mm a horn) for water colset squatting pan including jointing the trap with in in cement mortar (1:1) cutting the floor and mending good the mages etc all complete as per specification and direction of the gineer in charge Omm size Orissa pan(Parryware/Hindware/Neycer/Rak) Oplying all materials,labour, T&P and fixing the following vitreous has a wash down water closet Furongan type W.C. on the size of the polyman size or the size of the polyman type W.C. on the size of the polyman type W.C. on the size of the polyman type W.C. on the polyman type W.C. on the size of the polyman type W.C. on the polyman	2.00 Ea	ch	1279.90	2559.8
11 (C)	with fittings such as siphonic arrangements 15mm nominal size orass/pvc ball valve with polythene float CP brass handle, unions and couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including rutting holes and making good the same and connecting the flush bend with cistren and closet and connceting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in harge Ditres Capacity PVC cistren with 32mm dia flush bend carryware/Hindware/Neycer/Rak) applying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C pan/Orissa pattern squatting and only embedded in cement concrete (1:5:10) using 4cm size hard anite metal including fixing a pair of vitreous china 250mm x 130mm flootrest, fixing 100mm dia HCl 'p' or 's' trap (with/without 50mm a horn) for water colset squatting pan including jointing the trap with in in cement mortar (1:1) cutting the floor and mending good the mages etc all complete as per specification and direction of the gineer in charge Domm size Orissa pan(Parryware/Hindware/Neycer/Rak) polyling all materials,labour, T&P and fixing the following vitreous on a wash down water closet (European type W.C.pan) with integral 'P S' trap to the illor with wooden pluss and charging with integral 'P	2.00 Ea	ch	1279.90	2559.8
11 (GC) (GC) (GC) (GC) (GC) (GC) (GC) (GC)	with fittings such as siphonic arrangements 15mm nominal size orass/pvc ball valve with polythene float CP brass handle, unions and Couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including rutting holes and making good the same and connecting the flush bend with cistren and closet and connceting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in harge Ditres Capacity PVC cistren with 32mm dia flush bend diarryware/Hindware/Neycer/Rak) applying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C pan/Orissa pattern squatting and only duly embedded in cement concrete (1:5:10) using 4cm size hard anite metal including fixing a pair of vitreous china 250mm x 130mm footrest, fixing 100mm dia HCl 'p' or 's' trap (with/without 50mm a horn) for water colset squatting pan including jointing the trap with n in cement mortar (1:1) cutting the floor and mending good the mages etc all complete as per specification and direction of the gineer in charge Dimm size Orissa pan(Parryware/Hindware/Neycer/Rak) Doplying all materials, labour, T&P and fixing the following vitreous na wash down water closet (European type W.C.pan) with integral 'P S' trap to the illor with wooden plugs and chromium plated pedestal each including jointing the trap with soil plus in the following vitreous has wash down water closet (European type W.C.pan) with integral 'P	2.00 Ea	ch	1279.90	2559.8
11 (GC) (GC) (GC) (GC) (GC) (GC) (GC) (GC)	with fittings such as siphonic arrangements 15mm nominal size orass/pvc ball valve with polythene float CP brass handle, unions and Couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including rutting holes and making good the same and connecting the flush bend with cistren and closet and connceting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in harge Ditres Capacity PVC cistren with 32mm dia flush bend diarryware/Hindware/Neycer/Rak) upplying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C pan/Orissa pattern squatting and only embedded in cement concrete (1:5:10) using 4cm size hard anite metal including fixing a pair of vitreous china 250mm x 130mm footrest, fixing 100mm dia HCl 'p' or 's' trap (with/without 50mm a horn) for water colset squatting pan including jointing the trap with n in cement mortar (1:1) cutting the floor and mending good the mages etc all complete as per specification and direction of the gineer in charge Dimm size Orissa pan(Parryware/Hindware/Neycer/Rak) Doplying all materials, labour, T&P and fixing the following vitreous na wash down water closet (European type W.C.pan) with integral 'P S' trap to the illor with wooden plugs and chromium plated pedestal extra (1:1) fixing plastic seat and cover for weach diverged to cement retar(1:1) fixing plastic seat and cover for weach diverged to cement retar(1:1) fixing plastic seat and cover for weach diverged to cement	2.00 Ea	ch	1279.90	2559.8
11 (GC) (CC) (CC) (CC) (CC) (CC) (CC) (CC)	with fittings such as siphonic arrangements 15mm nominal size brass/pvc ball valve with polythene float CP brass handle, unions and Couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including utting holes and making good the same and connecting the flush bend with cistren and closet and connceting the inlet pipe with suupply main etc all omplete as per the specification and direction of the Engineer in harge O litres Capacity PVC cistren with 32mm dia flush bend 'arryware/Hindware/Neycer/Rak' upplying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C pan/Orissa pattern squatting an) duly embedded in cement concrete (1:5:10) using 4cm size hard anite metal including fixing a pair of vitreous china 250mm x 130mm Omm footrest, fixing 100mm dia HCl 'p' or 's' trap (with/without 50mm a horn) for water colset squatting pan including jointing the trap with n in cement mortar (1:1) cutting the floor and mending good the mages etc all complete as per specification and direction of the gineer in charge Omm size Orissa pan(Parryware/Hindware/Neycer/Rak) Deplying all materials, labour, T&P and fixing the following vitreous na wash down water closet (European type W.C.pan) with integral 'P S' trap to the illor with wooden plugs and chromium plated pedestal ews including jointing the trap with soil pipe in cement rtar(1:1) fixing plastic seat and cover for wash down water closet with omium plated brass hinges and rubbos buffer.	2.00 Ea	ch	1279.90	2559.8
11 (GC) (CC) (CC) (CC) (CC) (CC) (CC) (CC)	with fittings such as siphonic arrangements 15mm nominal size brass/pvc ball valve with polythene float CP brass handle, unions and Couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including utting holes and making good the same and connecting the flush bend with cistren and closet and connceting the inlet pipe with suupply main etc all omplete as per the specification and direction of the Engineer in harge O litres Capacity PVC cistren with 32mm dia flush bend 'arryware/Hindware/Neycer/Rak' upplying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C pan/Orissa pattern squatting an) duly embedded in cement concrete (1:5:10) using 4cm size hard anite metal including fixing a pair of vitreous china 250mm x 130mm Omm footrest, fixing 100mm dia HCl 'p' or 's' trap (with/without 50mm a horn) for water colset squatting pan including jointing the trap with n in cement mortar (1:1) cutting the floor and mending good the mages etc all complete as per specification and direction of the gineer in charge Omm size Orissa pan(Parryware/Hindware/Neycer/Rak) Deplying all materials, labour, T&P and fixing the following vitreous na wash down water closet (European type W.C.pan) with integral 'P S' trap to the illor with wooden plugs and chromium plated pedestal ews including jointing the trap with soil pipe in cement rtar(1:1) fixing plastic seat and cover for wash down water closet with omium plated brass hinges and rubbos buffer.	2.00 Ea	ch	1279.90	2559.8
11 (GC) (CC) (CC) (CC) (CC) (CC) (CC) (CC)	with fittings such as siphonic arrangements 15mm nominal size brass/pvc ball valve with polythene float CP brass handle, unions and Couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including utting holes and making good the same and connecting the flush bend with cistren and closet and connceting the inlet pipe with suupply main etc all omplete as per the specification and direction of the Engineer in harge O litres Capacity PVC cistren with 32mm dia flush bend 'arryware/Hindware/Neycer/Rak' upplying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C pan/Orissa pattern squatting an) duly embedded in cement concrete (1:5:10) using 4cm size hard anite metal including fixing a pair of vitreous china 250mm x 130mm Omm footrest, fixing 100mm dia HCl 'p' or 's' trap (with/without 50mm a horn) for water colset squatting pan including jointing the trap with n in cement mortar (1:1) cutting the floor and mending good the mages etc all complete as per specification and direction of the gineer in charge Omm size Orissa pan(Parryware/Hindware/Neycer/Rak) Deplying all materials, labour, T&P and fixing the following vitreous na wash down water closet (European type W.C.pan) with integral 'P S' trap to the illor with wooden plugs and chromium plated pedestal ews including jointing the trap with soil pipe in cement rtar(1:1) fixing plastic seat and cover for wash down water closet with omium plated brass hinges and rubbos buffer.	2.00 Ea	ch	1279.90	2559.8
11 (GC) (CC) (CC) (CC) (CC) (CC) (CC) (CC)	with fittings such as siphonic arrangements 15mm nominal size orass/pvc ball valve with polythene float CP brass handle, unions and Couplings for connection with inlet, outlet and overflow pipes, 32mm dia CP Long flush bend, 15mm dia pvc inlet connection pipe including rutting holes and making good the same and connecting the flush bend with cistren and closet and connceting the inlet pipe with suupply main etc all complete as per the specification and direction of the Engineer in harge Ditres Capacity PVC cistren with 32mm dia flush bend diarryware/Hindware/Neycer/Rak) upplying all materials, labour, T&P and fixing vitreous china water oset, squattingpan (Indian type W.C pan/Orissa pattern squatting and only embedded in cement concrete (1:5:10) using 4cm size hard anite metal including fixing a pair of vitreous china 250mm x 130mm footrest, fixing 100mm dia HCl 'p' or 's' trap (with/without 50mm a horn) for water colset squatting pan including jointing the trap with n in cement mortar (1:1) cutting the floor and mending good the mages etc all complete as per specification and direction of the gineer in charge Dimm size Orissa pan(Parryware/Hindware/Neycer/Rak) Doplying all materials, labour, T&P and fixing the following vitreous na wash down water closet (European type W.C.pan) with integral 'P S' trap to the illor with wooden plugs and chromium plated pedestal extra (1:1) fixing plastic seat and cover for weach diverged to cement retar(1:1) fixing plastic seat and cover for weach diverged to cement retar(1:1) fixing plastic seat and cover for weach diverged to cement	2.00 Ea	ch	1279.90	2559.8

Pe

ohe

W /

Ja. V

	European water algorithmith In the sale in the	-			185 13
	European water closet with 'P trap plain(Parryware/Hindware/Neycer/Rak)	1.00	Each	2427.00	2427.0
14	Supplying all materials, labour, T&P and fixing laboratory sink with outlet	1.00	Each	2427.90	2427.9
	at end and weir overfiow including fitting and fixing a pair of cast iron or				
	MS brackets painted white, fixing 50mm/40mm dia CP brass waste	1		05.31	and the second
	fixing 50mm/40mm dia PVC waste pipe 910mm long with supply of				
	wooden plugs,screws and cement etc including cutting holes in walls				
	and making good the damages etc all complete as per specification				
	and direction of the Engineer in charge.			20. 1	
	and direction of the Engineer in charge.				
	600mmx450mmx200mm size Stainless steel Sink	1.00	Each	2336.40	2336.4
15	Supplying all materials, labour T&P and fixing wash basins with hole for				
	pillar taps with cast iron or M.S.brackets painted white including cutting		5 H		
	holes in walls and making good the damages with supply of wooden				
	plugs, screws and cement etc, fixing pedestal for wash basin recessed		P 10 10		1 10
	550mmx400mm W.H.basin with porcelain pedestal & Jaquar make		h-		
	fittings(Parryware/Hindware/Neycer/Rak)	2.00	Each	3720.50	7441.0
16	Supplying all materials, labour, T&P and fixing mirror of superior glass				7.1.2.0
	mounted on 6mm thick A.C.sheet or plywood sheet and fixed to				
	WOoden plugs with CP screws and washers complete as per				
Y	specification and direction of the Engineer in charge				
7.0	600mmx450mm size B.E.mirror	2.00	Each	567.00	1134.0
17	Supplying all materials, labour, T&P and fixing standard size glassshelf with CP	2.00	Lucii	307.00	1134.0
	brass brackets and guard rails complete fixed to wooden	1			12 12 (2)
	plugs with CP screws as per specification and direction of the				1 1 2
	Engineer in charge			200	
	600mmx125mm glass shelf with CP/NP guard rails	2.00	E. J.	F0.4.00	
18	Supplying all materials, labour, T&P and fixing standard sized CP towel	2.00	Each	524.80	1049.6
	rail complete with CP brass brackets fixed to wooden plugs with CP SCrews as		S.		
	per specification and direction of the Engineer in charge		11 18		
-				, ,	
10	25mmx600mm long CP towel rail	2.00	Each	648.10	1296.20
19	Supplying all materials, labour, T&P and fixing CP soap holder	3.0 4	1.8.5	Hada	
	complete with CP brass brackets fixed to wooden plugs with CP screws			7.0	
	as per specification and direction of the Engineer in charge				
	CP soap holder				1,111
20	Supplying all materials, labour, T & P and constructing Gully trap	2.00	Each	142.10	284.20
	chamber of the following inside size with 8 and third B.	2.0		10	
	chamber of the following inside size with 8 cm thick R.C.c. precast			4 4 3	
	cover slab in CC (1:2:4) mix using 12mm size h.g. chips, foundation				
	concrete (1:4:8) using 40mm sizeh.g. metal on bed aound trap, K.B.				
	brickwork in CM (1:6) in P&F and inside 12mm thick cement plastering		-		
	(1:3) finished ith a floating coat of neat cement including fixing				
	100mm x100mm size gully trap, 150mm x150mm C.I gratig etc. all				
	complete as per aproved drawing, specification and direction of		, .		
	Engineer in charge				
	250mmx250mm with RCC cover	1.00	Each	1803.53	1803.53
21	Supplying all materials, labour, T & P and constructing Inspection				1000,00
	chamber of the following inside size with CC (1:3:6) mix using 40mm				
	size h.g. metal on bed, lst class K.B. brickwork in CM(1:6), moulding)			
	and shaping the channel inside and benching with CC (1:2:4) using				
	12mm size h.g. chips, 12mm thick cement plastering (1:3) finished with				
	punning to inside,cementflush pointing (1:3) to outside, R.C.C. cover				
	slab in (1:2:4) using 12mm size h.g. chips with RCC man hole cover,		ec 3		
	earth work in excavation in all kinds of soil and refilling the cavity				
	around the chamber including watering ,curing, conveyance of all				
	materials to worksite, payment of royality, taxes etc. all complete as				
	per aproved drawing, specification and direction of Engineer in charge	1	× 36		
	Inside size 760mm x760mm x460mm				1 12
	Inside Size 7 John A7 John A4 John III	1.00	Each	6503.06	6503.06

me sho

Ja

6

J.127

				Total	197282.29
		1.00	Each	1660.00	1660.00
	Supply and fitting &fixing of Plastic rope M.s cover cap etc	50.00	Mtr	71.70	3585.00
0	Supply and fitting &fixing of sustable cable and connecting the	50.00	Mtr	119.50	5975.00
0	County 10	F0.0-		1 1	
	set &testing etc				
, ,	Nippling and lowering to bore well making connection to pump			14/3.00	1475.00
29	Supply and fitting &fixing of HDPE Pipe and fitting with CP	1.00	Each	1475.00	4475 00
	Supply and fitting &fixing of I.S.I make 1.00 HP single phase submersible Pump with commissioning and testing	1.00	Lacii	15849.15	15849.15
28		1.00	Each	15040.45	
-	Supply and fitting &fixing of I.S.I make 1.00 HP single phase	43.00	IVIT	199.50	8977.5
27	Withdrawal of casing pipes	45.00	N/+=		o I
	I disaccessiul porpand denocitingin 4b - 1				20,3.0
26		0.20	cum	5368.00	1073.6
26	(CC(1:2:4) with 12mm chips for grouting upto 5 mts David		Each	789.80	789.8
	Sanitary sealing upto 5mtrs below ground level.				
	seamigle Actualing Cost of cement which will "			3.0	
	per direction of the Engineer in charge. Minimum one metre of casin9 pipe to be inserted in the bore into the rockthe bottom to ensure				
	drawing)to plug the bore hole excluding cost of cement all complete as per direction of the Engineer in charge. Mining				20 A
	The modeling pipe upto 5 mire halow ground in the				
	The state of the s		1 2		
-	Supplying all materials and labour,tools and plant and providing	,1.0	Lacii	4994.50	4994.
25	T - Thy Motory Mig	10	0 Each	4004 ==	2000
	Cleaing and developing the tube well with supply ofcompressor By DTH/Rotary Rig	30.0	olivitr	950.80	28524.
24	123 min did F.V.C Schedule-X() nine		00 Mtr 00 Mtr	138.20	
	Lowering of 125 mm dia GI/P.V.CMS casing pines 0 mts to 45	207	00 144:		
	of foreign material			9	
	and keeping the top of casing nine threaded in all it				
	"FF") "'B und living all jointing materials tools and "I-"				1
	acptif and fitted and fixed fin in perfectly venticel	* 1		it is	
	The state of the s		1		
23	Lowering the following size of G.I/P.V.C/M.S. bousing at	30.	00 Mtr	540.5	
22	Drilling of 150mm dia bore 31mtr to 60mtr		00 Mtr	540.5	0 1621
	Drilling of 200mm dia bore 0mtr to 30 mtr				
		5			
	supplied by the contractor for 400mm dia bore only	1			
	and in overbuideli portion including packing of annual	- 22			-
	and withdrawing diter completion of the tube of the			1	
	of the burden is to be provided by the contract and the		1	12 1	
					n ly
	or without well screen as per the necessity for soft, medium, hard and			7	
	tools and plant and consumables etc for lowering with its accessories, dia G.II/P.v.C/M.S casing pipes for housing fitted with socket and with or without well screen as parety.	-11 x - 2			
	The state of the s				
	as required to still the cite condition	- 10	- 21		
	unconsolidated rock with down the hole hammer drilling rig or	21 P		3 1 1	NI A
	specified depth below ground level through consolidated and				

me

pho

W/

200

اد No.	E.I. WORK					
YU.	Description of Itomo	Unit	Qnty	Rate		Amount
1	Recessed wiring to light point with 1.5 sq.mm FR PVC insulatedsingle core multistrand copper conductor of ISI marked with 20 mm dia non-metalic PVC flexible conduit with 5Amp, 250 V piano type modular switch ISI marked and ceiling rose ISI marked mounted on MS box having front Modular base & cover of suitable size , MS box with 1 sq.mm FR PVC insulated single core multistrand copper conductor as earth wire including all accesories and connection as per direction of Engineer in Charge. (Make of wire Finolex/ L&T / Anchor / Havels /HPL/ V Guard)					
а	-do- Group A	Point	15	463.38		6,950.6
b	-do- Group B	Point	9	688.68		6,198.1
С	-do- Gloup C	Point	8	970.14		7,761.0
2	Recessed wiring to Fan Point in	,				
_	-do- Group B	Point	6	688.68		4,132.0
3	Recessed wiring to Call Bell Point in					
<u> </u>	-do- Group C Recessed wiring to Exhaust Fan Point in	Point	1	970.14		970.1
_			_			
5	-do- Group B S/F of Angle holder replacing Ceilling Rose	_	3	688.68		2,066.0
	S/F of 5A. Modular Switch & 5A. Modular Socket outlet of ISI marked on existing board	Each	14	15.98		223.7
		Each	8	222.54	i 🗆	1,780.3
	connection, painting etc as required.	Each	6	763.97		4,583.8
		Each	4	636.08		2,544.3
	S/F of Power point with 4 modular & 2 modular metal box with modular base & cover in recess including providing and fixing of 5 pin 15/16 amp. piano type Modular switch & Socket & Mini DP MCB, connection, painting etc as required for AC	Each	1	1257.02		1,257.0
	S/F of 1 no of 5 pin 15/16 amp. Socket , 1 no of switch & 1 no of 15/16A top with modular mini MCB, in 6 modular box with cover with connection, painting etc as required for Inverter connection	Each	1	1174.01		1,174.0
	S/F of 18 SWG Modular metal box of following sizes (Nominal size) in recess with suitable size of Modular base & cover in front including cutting the wall and making good the same in case of recessed conduit as required.				į	
а	2 Modular box with base & cover				:	
h		Each	2	212.95		425.9
b	4 Modular box with base & cover	Each Each	1	212.95 260.24		7
С	4 Modular box with base & cover				-	260.24
c	4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover	Each Each	1	260.24		260.24 318.89
c d e	4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover	Each Each	1	260.24 318.89		260.2- 318.89 721.60
c d e	4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover Wiring for circuit / sub-main wiring along with earth wire with following sizes of PVC insulated single core	Each Each Each	1 1 2	260.24 318.89 360.83		260.24 318.88 721.66
d e 12 a	4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover Wiring for circuit / sub-main wiring along with earth wire with following sizes of PVC insulated single core 2x1.5+1x1.0 (1.8)	Each Each Each Mtrs	1 2 7 52	260.24 318.89 360.83 473.49		260.24 318.89 721.60 3,314.45
d e 12 a b	4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover Wiring for circuit / sub-main wiring along with earth wire with following sizes of PVC insulated single core 2x1.5+1x1.0 (1.8) 2x1.5+1x1.5 (1.8.1);	Each Each Mtrs Mtrs	1 1 2 7 52 90	260.24 318.89 360.83 473.49 125.05 126.07		260.24 318.89 721.60 3,314.43 6,502.60 11,346.30
d e l2 a b	4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover Wiring for circuit / sub-main wiring along with earth wire with following sizes of PVC insulated single core 2x1.5+1x1.0 (1.8) 2x1.5+1x1.5 (1.8.1); 2x2.5+1x1.5 (1.8.2)	Each Each Mtrs Mtrs Mtrs	1 1 2 7 52 1 90 1 85	260.24 318.89 360.83 473.49 125.05 126.07 140.03		260.24 318.89 721.60 3,314.43 6,502.60 11,346.30 11,902.53
d e 12 a b	4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover Wiring for circuit / sub-main wiring along with earth wire with following sizes of PVC insulated single core 2x1.5+1x1.0 (1.8) 2x1.5+1x1.5 (1.8.1); 2x2.5+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.3);	Each Each Mtrs Mtrs Mtrs Mtrs	1 1 2 7 52 90 85 85 85	260.24 318.89 360.83 473.49 125.05 126.07 140.03 157.41		260.2· 318.8 721.6 3,314.4: 6,502.6 11,346.3 11,902.5 13,379.8
d e 12 a b c	4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover Wiring for circuit / sub-main wiring along with earth wire with following sizes of PVC insulated single core 2x1.5+1x1.0 (1.8) 2x1.5+1x1.5 (1.8.1); 2x2.5+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.3) 2x6+1x2.5 (1.8.4)	Each Each Mtrs Mtrs Mtrs Mtrs Mtrs	1 1 2 7 52 90 85 85 72	260.24 318.89 360.83 473.49 125.05 126.07 140.03 157.41 188.49		260.2· 318.8 721.6 3,314.4· 6,502.6 11,346.3 11,902.5 13,379.8 13,571.2
d e I2 a b c d e F	4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover Wiring for circuit / sub-main wiring along with earth wire with following sizes of PVC insulated single core 2x1.5+1x1.0 (1.8) 2x1.5+1x1.0 (1.8) 2x1.5+1x1.5 (1.8.1) 2x2.5+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.3) 2x6+1x2.5 (1.8.4) Inverter wiring (1x1.5smm) Copper wire (1.19.1) S/F of 'B/C/D' series SP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for lighting and other loads in the existing MCB Distribution board ISI marked complete with connection	Each Each Mtrs Mtrs Mtrs Mtrs Mtrs	1 1 2 7 52 90 85 85 85	260.24 318.89 360.83 473.49 125.05 126.07 140.03 157.41		260.2· 318.8 721.6 3,314.4· 6,502.6 11,346.3 11,902.5 13,379.8 13,571.2 3,437.2
c d e 2 a b c d e F 3	4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover Wiring for circuit / sub-main wiring along with earth wire with following sizes of PVC insulated single core 2x1.5+1x1.0 (1.8) 2x1.5+1x1.0 (1.8) 2x2.5+1x1.5 (1.8.1) 2x2.5+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.3) 2x6+1x2.5 (1.8.4) Inverter wiring (1x1.5smm) Copper wire (1.19.1) S/F of 'B/C/D' series SP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for lighting and other loads in the existing MCB Distribution board ISI marked complete with connection, testing and commissioning etc. as required single pole (SP) (2.6.1) S/F of 'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for lighting and other loads in the 2 Way double door MCB Distribution board ISI marked complete with connection, testing and commissioning etc. as required (2.6.2a)+(2.3.1b)	Each Each Mtrs Mtrs Mtrs Mtrs Mtrs Mtrs Mtrs	1 1 2 7 52 90 85 85 72 75 1	260.24 318.89 360.83 473.49 125.05 126.07 140.03 157.41 188.49 45.83		260.2· 318.8 721.6 3,314.4· 6,502.6 11,346.3 11,902.5 13,379.8 13,571.2 3,437.2 1,041.2
c d e 2 a b c d e F 3 4	4 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover Wiring for circuit / sub-main wiring along with earth wire with following sizes of PVC insulated single core 2x1.5+1x1.0 (1.8) 2x1.5+1x1.5 (1.8.1); 2x2.5+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.3) 1nverter wiring (1x1.5smm) Copper wire (1.19.1); S/F of 'B/C/D' series SP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for lighting and other loads in the existing MCB Distribution board ISI marked complete with connection, testing and commissioning etc. as required single pole (SP) (2.6.1) S/F of 'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for lighting and other loads in the 2 Way double door MCB Distribution board ISI marked complete with connection, testing and commissioning etc. as required (2.6.2a)+(2.3.1b) Supply, Installation testing & commissioning of Main Switches (IS13940 part 3/1993) of following coopacity on existing surface/wall mounting & complete with H.R.C fuse links, inter connections earthing etc as required as per direction of Engineer Incharge (Make-Seimens/HPL/Anchor/L&T /Havels/C&S/R. K.)	Each Each Mtrs Mtrs Mtrs Mtrs Mtrs Each	1 1 2 7 52 90 85 85 72 75 8	260.24 318.89 360.83 473.49 125.05 126.07 140.03 157.41 188.49 45.83		260.24 318.89 721.66 3,314.40 6,502.66 11,346.30 11,902.55 13,379.85 13,571.28 3,437.25
d e 12 a b c d e F 13	4 Modular box with base & cover 6 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover Wiring for circuit / sub-main wiring along with earth wire with following sizes of PVC insulated single core 2x1.5+1x1.0 (1.8) 2x1.5+1x1.5 (1.8.1); 2x2.5+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.3) 2x6+1x2.5 (1.8.4) Inverter wiring (1x1.5smm) Copper wire (1.19.1)' S/F of 'B/C/D' series SP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for lighting and other loads in the existing MCB Distribution board ISI marked complete with connection, testing and commissioning etc. as required single pole (SP) (2.6.1) S/F of 'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for lighting and other loads in the 2 Way double door MCB Distribution board ISI marked complete with connection, testing and commissioning etc. as required (2.6.2a)+(2.3.1b) Supply, Installation testing & commissioning of Main Switches (IS13940 part 3/1993) of following coopacity on existing surface/wall mounting & complete with H.R.C fuse links, inter connections earthing etc as required as per direction of Engineer Incharge (Make-Seimens/HPL/Anchor/L&T /Havels/C&S/R. K.) S/F of MCB 8 way Double door (2.3.6)	Each Each Mtrs Mtrs Mtrs Mtrs Mtrs Each	1 1 2 7 52 90 85 85 72 75 8	260.24 318.89 360.83 473.49 125.05 126.07 140.03 157.41 188.49 45.83		260.24 318.89 721.66 3,314.43 6,502.60 11,346.30 11,902.55 13,379.85 13,571.28 3,437.25 1,041.28
d e 12 a b c d e F 13	4 Modular box with base & cover 8 Modular box with base & cover 12 Modular box with base & cover 12 Modular box with base & cover Wiring for circuit / sub-main wiring along with earth wire with following sizes of PVC insulated single core 2x1.5+1x1.0 (1.8) 2x1.5+1x1.5 (1.8.1); 2x2.5+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.2) 2x4+1x1.5 (1.8.3) 1nverter wiring (1x1.5smm) Copper wire (1.19.1); S/F of 'B/C/D' series SP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for lighting and other loads in the existing MCB Distribution board ISI marked complete with connection, testing and commissioning etc. as required single pole (SP) (2.6.1) S/F of 'B/C/D' series DP MCB of 5 - 32A amp rating (As per direction of engineer in charge) 240Volt for lighting and other loads in the 2 Way double door MCB Distribution board ISI marked complete with connection, testing and commissioning etc. as required (2.6.2a)+(2.3.1b) Supply, Installation testing & commissioning of Main Switches (IS13940 part 3/1993) of following coopacity on existing surface/wall mounting & complete with H.R.C fuse links, inter connections earthing etc as required as per direction of Engineer Incharge (Make-Seimens/HPL/Anchor/L&T /Havels/C&S/R. K.)	Each Each Mtrs Mtrs Mtrs Mtrs Mtrs Each	1	260.24 318.89 360.83 473.49 125.05 126.07 140.03 157.41 188.49 45.83 130.16		425.90 260.24 318.89 721.66 3,314.43 6,502.60 11,346.30 11,902.55 13,379.85 13,571.28 3,437.25 1,041.28 717.10

очириу & laying 6 SWG G.I. wire in re

Le

SI.	Description of Items	Unit	Qnty	Rate		Amount
18	Providing & fixing plain 16/0.2mm twin twisted flexible, FR PVC insulated copper cable in polythene sleeve or conduit of suitable size on the floor/wall or side of the table/door etc as required.(1.31)	Mtrs	4	18.00		72.00
19	Supply, Installation, Testing & Commissioning of exhaust fan upto 450 mm sweep in the exising opening, including making the hole to suit the size of the above fan making good the damaged complete,	Each	2	1970.33		3,940.66
20	5/F of Call bell/buzzer(billing doing type)	Each	1	120.00		120.00
21	as required. (1.30) S/F of 18-25Watt L.E.D Tube light fitting with all accessories and connections (Make:HPL-Neptune	Each	14	683.00		9,562.00
22	Supply of 1200mm A.C. Ceiling fan with all accessories and connections with out fan regulator (Make:Usha-Striker Millenium/Crompton-Jura /Anchor-XL/Havels-Velocity/Spark/Orient-Summer pride)	Each	7	2425.00		16,975.00
23	S/F step type fan regulator	Each	7	377.00		2,639.00
	Supply & fixing of superior type C.I bulk head fitting with 9W Led Bulb for general domestic use ISI marked square / oval type with premetallic glass cover provided with galvanized steel wire guard including	Each	1	587.00	0	587.00
25	necessary connections. (M-5) Supply & Fixing of 20-25Watt single L.E.D street light fitting with LED & Electrinic driver including all	Each	1	2878.00		2,878.00
26	accessories and connections (Make:Crompton/Phillips/HPL/Polycab/Havells) Supply & Fixing of 30-35Watt single L.E.D street light fitting with LED & Electrinic driver including all	Each	1	3402.00		3,402.00
	accessories and connections (Make:Crompton/Phillips/HPL/Polycab/Havens)	Each	1 1	5706.00		5,706.00
2	accessories and connections (Make:Crompton/Phillips/HPL/Polycab/Havells) S/F of electronic 9w Watt LED Bulb	Each	12	169.65		2,035.80
2	S/F of fan hook 'S' type made of 16 mm MS rod for fixing in the Existing RCC Roof.	Eacl	7	241.00		1,687.0
3	S/E of 6 sqmm twin core unbonded aluminium service connection wire with no.10 G.I. Guard wire to	Mtrs	45	42.00		1,890.0
3	support the aluminium wire S/F of 5KVA stabilizer 110V to 230V(V guard/ Shakti) with angle frame to rest the stabilizer	Eac	h 1	17024.00		17,024.0
١_,	2 Provision of 40mm dia HDPE pipe for laying & protection of cable	Mtr	S !	120.00		
	3 S/F of Main incoming switch box i) 63A DP MCCB-1 no ii) 63A DP RCCB- 1no iii) 275V,20KA SPD 1no	LS	1	15408.00		15,408.0
L	iv) 63A Bus bar			TOTAL		196,601.7
L				Say RS		196601.0

me appa

Jacky John J

2.12.