



Letter NO: 1999/HSS/2021-22

Dated: 14/02/2022

Quotation Call Notice

Sealed quotations are invited from the registered suppliers for supply of different item of Open air gym for PHC Barikumpa, under CDM&PHO, Phulbani Kandhamal.


The supplier has to submit their quotations in sealed covers which must be super-scribed as “**supply of different item for Open Air Gym,**”.

Technical Bid should contain as follows:

1. The document should be **serially arranged** and should be securely tied and bound.
2. Copies of organization PAN.
3. Photocopy of the GST Registration Certificate.
4. All the quotation documents should sign by the supplier at the bottom of each page with his official seal duly affixed.
5. They should quote the rates for individual items inclusive of excise duty, insurance, packing, forwarding, freight (door delivery) and GST charges (if any).
6. The rate should be under approved rate of Govt. of Odisha.
7. Financial Bid must be submitted in the prescribed format as attached in **Annexure- A**.
8. The rates should be computerized.


Eligible bidders should submit their quotation documents to the CDM & PHO, kandhamal through **Speed Post / Registered Post/ courier on or before 22.02.2022 by 05.00 P.M and will be opened on the same day i.e. 22.02.2022 at 05.30 PM.**

The undersigned reserves the right to reject or cancel any or all the quotations without assigning any reason thereof.


Chief District Medical & Public Health Officer
Kandhamal

Memo No: 2000 / HSS / 2021-22 Dated: 14 / 02 / 2022

1. Copy to notice board of all District officers of kandhamal District for information and wide publicity.
2. Copy to the DIO, NIC, Kandhamal for information with a request to publish the same in the district website.


Chief District Medical & Public Health Officer
Kandhamal



Annexure – A

SI. No.	Name	Specification	Unit	Rate (Rs.)
1	Hip Shaper	<p>Type: Skier (Double)</p> <p>Size Length: 1200 millimeter or more Width :-700 millimeter or more Height: 1300 millimeter or more</p> <p>Capacity Maximum user weight in Kg: 100 Kilogram</p> <p>Material Governing Specification for GI Pipes BIS specification No IS 1161:2014, latest All the GI Pipes are ISI marked: Yes Main Central Pipe: 150mm Nominal Bore G.I. Pipe Main Central Pipe, Class as per IS 1239 Heavy Designation of Main Central Pipe (as per IS 1161) Handle Frame: 40mm Nominal bore G.I. pipe Handle Frame Pipe, Class as per IS 1239 Heavy Designation of Handle Frame Pipe (as per IS 1161): 40 NB GI PIPE Foot Rest: Aluminum casting material Foot Rest Pipe: 32mm Nominal Bore G.I. Pipe Foot Rest Pipe, Class as per IS 1239: Medium/Heavy Designation of Foot Rest Pipe (as per IS 1161): 32 NB GI PIPE MS Foundation Plate Thickness: 12 millimeter Foundation Pipes with anchoring : 500mm deep GI Pipe, supported with M.S. Angle 25 X 25 X 4mm Nominal Bore of Foundation Pipe: 100mm Foundation Pipe, Class as per IS 1239: Medium Designation of Foundation Pipe (as per IS 1161): 100 NB GI PIPE Galvanization of all Pipes : Zinc coating on the tubes shall be in accordance with IS 4736 latest. Hand Grips: Rubber Nuts and Bolts for Assembly: G.I. Movement must be supplied with bearings: Yes Bearings: Tapered Roller Bearing Bearings shall be self lubricating and sealed for protection against Rain and dust etc: Yes Closing Caps of open ends of the pipes, bearings, bushes and base HDPE Thickness of closing caps (min): 3 millimeter All Plastic components UV stabilised, Weather resistance. COLOUR Colour As per buyer's requirements Paint/ Finish Powder Coated, UV resistant Paint Coating Thickness (min): 100 micrometer</p> <p>OTHER REQUIREMENTS Ergonomic Design: Yes Moving Scope should be Limited: Yes</p> <p>CERTIFICATION Certification (Safety and Quality Requirements) As per European</p>	Each	



		Standard EN 16630/BIS/ASTM Manufacturer should be ISO certified WARRANTY Warranty (years): 3 year Colour Green		
2	Rowing	Permanently installed outdoor fitness equipment. Dimensions Of Equipment : 1280 X 800 X 1150 approximate Epoxy coating of at least 100 micron to prevent any damage from weather conditions. UV resistant. Thick galvanized main post of 125 mm diameter. Thickness of pipes varies between 3.5 mm to 5.5 mm. Self lubricating Tapped Roller bearing for maintenance free usage. Reinforced foot pedals for extended life. J hook system with 18 mm thickness used for grouting for stability and ease of installation. Non fading Virgin LLDPE/HDPE makes all plastic components sun fade resistant. All open ends of pipe either sealed in or closed by GI/LLDPE cap for user safety. Certification (Safety and Quality Requirements) As per European Standard EN 16630/BIS/ASTM Manufacturer should be ISO certified WARRANTY Warranty (years): 3 year Colour Green	Each.	

Signature of the Bidder with seal

19/21/2023